

ISO 16486-3:2012-06 (E)

Plastics piping systems for the supply of gaseous fuels - Unplasticized polyamide (PA-U) piping systems with fusion jointing and mechanical jointing - Part 3: Fittings

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms, definitions, symbols and abbreviated terms	2
4	Material	3
4.1	PA-U compound	3
4.2	Material for non-unplasticized polyamide parts	3
5	General characteristics	4
5.1	Appearance	4
5.2	Design	4
5.3	Colour	4
5.4	Electrical characteristics for electrofusion fittings	4
5.5	Appearance of factory-made joints	4
5.6	Fusion compatibility	4
6	Geometrical characteristics	5
6.1	Measurement of dimensions	5
6.2	Dimensions of electrofusion sockets	5
6.3	Dimensions of spigot end fittings	7
6.4	Dimensions of tapping tees	8
6.5	Dimensions of transition fittings to other materials	9
7	Mechanical characteristics	9
7.1	General	9
7.2	Conditioning	9
7.3	Requirements	9
8	Physical characteristics	10
8.1	Conditioning	10
8.2	Requirement	11
9	Chemical resistance of fittings in contact with chemicals	11
10	Performance requirements	11
11	Marking	11
11.1	General	11
11.2	Minimum required marking of fittings	11
11.3	Additional information required on fitting or label	12
11.4	Fusion system recognition	12
12	Packaging	12
Annex A (informative)	Examples of typical terminal connections for electrofusion fittings	13

Annex B (normative) Short-term pressure test method	15
Annex C (normative)Tensiletestfitting/pipeassemblies	17
Bibliography	18