

DIN EN ISO 5659-2:2013-03 (E)

Plastics - Smoke generation - Part 2: Determination of optical density by a single-chamber test (ISO 5659-2:2012)

Contents		Page
Foreword		
Introduction		
1	Scope	
2	Normative references	
3	Terms and definitions	
4	Principles of the test	
5	Suitability of a material for testing	
5.1	Material geometry	
5.2	Physical characteristics	
6	Specimen construction and preparation	
6.1	Number of specimens	
6.2	Size of specimens	
6.3	Specimen preparation	
6.4	Wrapping of specimens	
6.5	Conditioning	
7	Apparatus and ancillary equipment	
7.1	General	
7.2	Test chamber	
7.3	Specimen support and heating arrangements	
7.4	Gas supply	19
7.5	Photometric system	
7.6	Chamber leakage	
7.7	Cleaning materials	
7.8	Ancillary equipment	
8	Test environment	
9	Setting-up and calibration procedures	
9.1	General	
9.2	Alignment of photometric system	
9.3	Selection of compensating filter(s)	
9.4	Linearity check	25
9.5	Calibration of range-extension filter	25
9.6	Chamber leakage rate test	25
9.7	Burner calibration	25
9.8	Radiator cone calibration	26
9.9	Cleaning	26
9.10	Frequency of checking and calibrating procedure	26
10	Test procedure	27
10.1	General	27
10.2	Preparation of test chamber	27
10.3	Tests with pilot flame	27

10.4	Preparation of the photometric system	27
10.5	Loading the specimen	27
10.6	Recording of light transmission	28
10.7	Observations	28
10.8	Termination of test	29
10.9	Testing in different modes	29
11	Expression of results	
11.1	Specific optical density D_s	
11.2	Clear-beam correction factor D_c	
10	10 10 14 20 22 22 24 24 30 30 30 12 Precision	
13	Test report	
Annex A (normative) Calibration of heat fluxmeter		
Annex B (informative) Variability in the specific optical density of smoke measured in the single-chamber test		
Annex C (informative) Determination of mass optical density		
		35
Annex D (informative) Precision data from tests on intumescent materials		
Annex E (informative) Guidance on optical density testing		
Bibliography		