

DIN EN ISO 307:2013-08 (E)

Plastics - Polyamides - Determination of viscosity number (ISO 307:2007 + Amd 1:2013) (includes Amendment :2013)

| Contents | Page |
|--|-------------|
| Introduction | 4 |
| 1 Scope | 5 |
| 2 Normative references | 5 |
| 3 Terms and definitions | 6 |
| 4 Principle | 7 |
| 5 Reagents and materials | 7 |
| 5.1 Solvents and reagents | 7 |
| 5.2 Cleaning liquids | 8 |
| 6 Apparatus | 8 |
| 7 Preparation of test samples | 9 |
| 7.1 General | 9 |
| 7.2 Samples containing less than 98 % (by mass) polyamide | 9 |
| 8 Calculation of test portion | 10 |
| 9 Selection of solvent | 10 |
| 10 Procedure | 11 |
| 10.1 Cleaning of the viscometer | 11 |
| 10.2 Preparation of test solution | 11 |
| 10.3 Measurement of flow times | 13 |
| 11 Expression of results | 14 |
| 12 Repeatability and reproducibility | 14 |
| 13 Relationship between the viscosity number determined in 96 % (by mass) sulfuric acid solution and the viscosity determined in various solvents | 15 |
| 14 Test report | 15 |
| Annex A (informative) Determination of the concentration of commercial sulfuric acid (95 % to 98 %) and adjustment to 96 % by titration | 17 |
| Annex B (informative) Determination of the concentration of sulfuric acid (95 % to 98 %) and adjustment to 96 % by flow time measurement in a small capillary viscometer | 20 |
| Annex C (informative) Determination of the concentration of commercial formic acid and adjustment to 90 % by titration | 22 |
| Annex D (informative) Determination of the concentration of commercial formic acid and adjustment to 90 % by density measurement | 24 |
| Annex E (informative) Relationship between the viscosity number determined in 96 % (by mass) sulfuric acid solution and the viscosity determined in various solvents | 27 |
| Bibliography | 37 |