

ISO 17484-1:2014-06 (E)

**Plastics piping systems - Multilayer pipe systems for indoor gas installations with a maximum operating pressure up to and including 5 bar (500 kPa) - Part 1:
Specifications for systems**

Contents

	Page
Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms, definitions and symbols	2
3.1 Structural definitions	3
3.2 Geometrical definitions	3
3.3 Definitions related to pressure	4
3.4 Materials definitions	4
3.5 Definitions related to material characteristics	5
3.6 Terms related to service conditions	5
4 Requirements for the system	6
4.1 Pressure drop	6
4.2 Bending	6
4.3 Corrosive conditions	6
5 Pipes	6
5.1 Materials	6
5.2 General characteristics	6
5.3 Dimensions of pipes	7
5.4 Mechanical properties	7
5.5 Physical properties	8
6 Fittings	9
6.1 General	9
6.2 Materials	10
6.3 Dimensions of fittings	10
6.4 Transition fittings	10
6.5 Rubber rings	10
7 Fitness for purpose	10
7.1 Diameter classes	10
7.2 Requirements	10
8 Marking and documentation	13
8.1 Legibility	13
8.2 Damage	13
8.3 Minimum required marking	13
8.4 Additional Instructions	13
Annex A (normative) List of the reference product standards	14
Annex B (normative) Test for delamination and strength of the joint line	15

Annex C (normative) Resistance to gas constituents	17
Annex D (normative) Thermal durability of the outer layer of M-pipes	19
Annex E (normative) Adhesion test	21
Annex F (normative) Odour permeability	22
Annex G (normative) Resistance to tensile load on joints	23
Annex H (normative) Crush test on joints	25
Annex I (normative) Impact resistance test on joints	27
Annex J (normative) Thermal cycling test on joints	29
Annex K (normative) Repeated bending test	31
Bibliography	33