

# ISO 17541:2014-09 (E)

## Plastics - Quantitative evaluation of scratch-induced damage and scratch visibility

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Principle .....</b>	<b>3</b>
<b>5</b>	<b>Apparatus .....</b>	<b>3</b>
5.1	General description .....	3
5.2	Scratch tip .....	3
5.3	Load and position sensors .....	4
5.4	Test load .....	4
5.5	Test speed .....	4
5.6	Specimen stage .....	4
<b>6</b>	<b>Test specimens .....</b>	<b>5</b>
6.1	General .....	5
6.2	Shape and dimensions .....	5
6.3	Preparation .....	5
6.4	Conditioning .....	5
6.5	Number of test specimens .....	5
<b>7</b>	<b>Procedure .....</b>	<b>5</b>
7.1	Test atmosphere .....	5
7.2	Scratch tip .....	5
7.3	Method A (constant load condition) .....	5
7.4	Method B (linearly increasing load condition) .....	6
7.5	Scratch testing .....	6
<b>8</b>	<b>Interpretation of result .....</b>	<b>7</b>
8.1	General .....	7
8.2	Scratch strength and scratch resistance .....	7
8.3	Single-damage (SD) .....	7
8.4	Multiple-damage (MD) .....	8
<b>9</b>	<b>Test report .....</b>	<b>10</b>
<b>Annex A (informative) 3-D colour model .....</b>		<b>12</b>
<b>Annex B (informative) Example for quantitative determination of scratch damage and scratch visibility .....</b>		<b>13</b>
<b>Bibliography .....</b>		<b>17</b>