

# ISO 17541:2014-09 (E)

## Plastics - Quantitative evaluation of scratch-induced damage and scratch visibility

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Principle .....</b>	<b>3</b>
<b>5</b>	<b>Apparatus .....</b>	<b>3</b>
<b>5.1</b>	<b>General description .....</b>	<b>3</b>
<b>5.2</b>	<b>Scratch tip .....</b>	<b>3</b>
<b>5.3</b>	<b>Load and position sensors .....</b>	<b>4</b>
<b>5.4</b>	<b>Test load .....</b>	<b>4</b>
<b>5.5</b>	<b>Test speed .....</b>	<b>4</b>
<b>5.6</b>	<b>Specimen stage .....</b>	<b>4</b>
<b>6</b>	<b>Test specimens .....</b>	<b>5</b>
<b>6.1</b>	<b>General .....</b>	<b>5</b>
<b>6.2</b>	<b>Shape and dimensions .....</b>	<b>5</b>
<b>6.3</b>	<b>Preparation .....</b>	<b>5</b>
<b>6.4</b>	<b>Conditioning .....</b>	<b>5</b>
<b>6.5</b>	<b>Number of test specimens .....</b>	<b>5</b>
<b>7</b>	<b>Procedure .....</b>	<b>5</b>
<b>7.1</b>	<b>Test atmosphere .....</b>	<b>5</b>
<b>7.2</b>	<b>Scratch tip .....</b>	<b>5</b>
<b>7.3</b>	<b>Method A (constant load condition) .....</b>	<b>5</b>
<b>7.4</b>	<b>Method B (linearly increasing load condition) .....</b>	<b>6</b>
<b>7.5</b>	<b>Scratch testing .....</b>	<b>6</b>
<b>8</b>	<b>Interpretation of result .....</b>	<b>7</b>
<b>8.1</b>	<b>General .....</b>	<b>7</b>
<b>8.2</b>	<b>Scratch strength and scratch resistance .....</b>	<b>7</b>
<b>8.3</b>	<b>Single-damage (SD) .....</b>	<b>7</b>
<b>8.4</b>	<b>Multiple-damage (MD) .....</b>	<b>8</b>
<b>9</b>	<b>Test report .....</b>	<b>10</b>
<b>Annex A (informative) 3-D colour model .....</b>		<b>12</b>
<b>Annex B (informative) Example for quantitative determination of scratch damage and scratch visibility .....</b>		<b>13</b>
<b>Bibliography .....</b>		<b>17</b>