

DIN EN 1815:2016-12 (E)

Resilient and laminate floor coverings - Assessment of static electrical propensity

| Contents | | Page |
|--|---|-------------|
| European foreword | | 3 |
| 1 | Scope | 4 |
| 2 | Normative References | 4 |
| 3 | Terms and definitions | 4 |
| 4 | Principle | 4 |
| 5 | Apparatus | 4 |
| 5.1 | Substructure for resilient floor coverings | 4 |
| 5.2 | Substructure for laminate floor coverings | 4 |
| 5.2.1 | Laminate floor coverings without attached sound absorbing material | 4 |
| 5.2.2 | Laminate floor coverings with attached sound absorbing material | 4 |
| 5.3 | Test sandals | 5 |
| 5.4 | Means of cleaning the sandals | 6 |
| 5.5 | Ionizing source | 6 |
| 5.6 | Body voltage measuring system | 6 |
| 5.7 | Thermometer and hygrometer | 7 |
| 6 | Conditioning | 7 |
| 7 | Test procedure | 7 |
| 7.1 | Cleaning of test sandals | 7 |
| 7.2 | Method A: test procedure in laboratory conditions | 8 |
| 7.2.1 | Preparation | 8 |
| 7.2.2 | Discharging | 8 |
| 7.2.3 | Walking test | 8 |
| 7.3 | Method B: test procedure in situ | 8 |
| 8 | Calculation and expression of results | 8 |
| 9 | Test report | 10 |
| 10 | Precision | 10 |
| Annex A (informative) Precision of the method | | 11 |