

DIN EN ISO 4674-1:2017-03 (E)

Rubber- or plastics-coated fabrics - Determination of tear resistance - Part 1: Constant rate of tear methods (ISO 4674-1:2016)

| Contents | Page |
|---|-------------|
| European foreword..... | 3 |
| Foreword..... | 4 |
| Introduction..... | 5 |
| 1 Scope | 6 |
| 2 Normative references | 6 |
| 3 Terms and definitions | 6 |
| 4 Apparatus and reagents | 7 |
| 5 Atmospheres for conditioning and testing | 7 |
| 5.1 For conditioning..... | 7 |
| 5.2 For testing..... | 7 |
| 6 Time-interval between manufacture and testing | 7 |
| 7 Method A — Tongued (double-tear) test piece | 7 |
| 7.1 Selection and preparation of test pieces..... | 7 |
| 7.2 Procedure..... | 9 |
| 7.3 Calculation and expression of results..... | 10 |
| 7.3.1 Trace with a series of definite peaks..... | 10 |
| 7.3.2 Trace without definite peaks..... | 10 |
| 8 Method B — Trouser-shaped (single-tear) test piece | 11 |
| 8.1 Selection and preparation of test pieces..... | 11 |
| 8.2 Procedure..... | 12 |
| 8.3 Calculation and expression of results..... | 13 |
| 9 Precision | 13 |
| 10 Test report | 13 |
| Annex A (informative) Example of calculation of tear force | 14 |
| Annex B (normative) Wide-width trouser-shaped test piece | 16 |