

# DIN EN ISO 4674-1:2017-03 (E)

## Rubber- or plastics-coated fabrics - Determination of tear resistance - Part 1: Constant rate of tear methods (ISO 4674-1:2016)

---

| <b>Contents</b>   | <b>Page</b> |
|---|-------------|
| European foreword.....  | 3           |
| Foreword.....   | 4           |
| Introduction.....   | 5           |
| <b>1 Scope</b> .....  | <b>6</b>    |
| <b>2 Normative references</b> .....                                     | <b>6</b>    |
| <b>3 Terms and definitions</b> .....                                    | <b>6</b>    |
| <b>4 Apparatus and reagents</b> .....                                   | <b>7</b>    |
| <b>5 Atmospheres for conditioning and testing</b> .....                 | <b>7</b>    |
| 5.1 For conditioning.....   | 7           |
| 5.2 For testing.....  | 7           |
| <b>6 Time-interval between manufacture and testing</b> .....            | <b>7</b>    |
| <b>7 Method A — Tongued (double-tear) test piece</b> .....              | <b>7</b>    |
| 7.1 Selection and preparation of test pieces.....                       | 7           |
| 7.2 Procedure.....  | 9           |
| 7.3 Calculation and expression of results.....                          | 10          |
| 7.3.1 Trace with a series of definite peaks.....                        | 10          |
| 7.3.2 Trace without definite peaks.....                                 | 10          |
| <b>8 Method B — Trouser-shaped (single-tear) test piece</b> .....       | <b>11</b>   |
| 8.1 Selection and preparation of test pieces.....                       | 11          |
| 8.2 Procedure.....  | 12          |
| 8.3 Calculation and expression of results.....                          | 13          |
| <b>9 Precision</b> .....  | <b>13</b>   |
| <b>10 Test report</b> .....   | <b>13</b>   |
| <b>Annex A (informative) Example of calculation of tear force</b> ..... | <b>14</b>   |
| <b>Annex B (normative) Wide-width trouser-shaped test piece</b> .....   | <b>16</b>   |