

# ISO 1421:2016-12 (E)

## Rubber- or plastics-coated fabrics - Determination of tensile strength and elongation at break

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Principle .....</b>	<b>5</b>
<b>5</b>	<b>Apparatus and reagents .....</b>	<b>5</b>
<b>6</b>	<b>Atmosphere for conditioning and testing .....</b>	<b>6</b>
<b>6.1</b>	<b>For conditioning .....</b>	<b>6</b>
<b>6.2</b>	<b>For testing .....</b>	<b>6</b>
<b>7</b>	<b>Time-interval between manufacture and testing .....</b>	<b>6</b>
<b>8</b>	<b>Method 1: Strip test method .....</b>	<b>6</b>
<b>8.1</b>	<b>Sampling and preparation of test pieces .....</b>	<b>6</b>
<b>8.2</b>	<b>Procedure .....</b>	<b>7</b>
<b>8.2.1</b>	<b>Mounting the test piece in place .....</b>	<b>7</b>
<b>8.2.2</b>	<b>Operation .....</b>	<b>9</b>
<b>8.2.3</b>	<b>Slippage .....</b>	<b>9</b>
<b>8.2.4</b>	<b>Jaw breaks and the breaks outside the reference marks .....</b>	<b>9</b>
<b>8.2.5</b>	<b>Test on wet test pieces .....</b>	<b>9</b>
<b>8.3</b>	<b>Calculation and expression of results .....</b>	<b>10</b>
<b>8.4</b>	<b>Test report .....</b>	<b>10</b>
<b>9</b>	<b>Method 2: Grab test method .....</b>	<b>10</b>
<b>9.1</b>	<b>Sampling and preparation of test pieces .....</b>	<b>10</b>
<b>9.2</b>	<b>Procedure .....</b>	<b>11</b>
<b>9.2.1</b>	<b>Mounting the test piece in place .....</b>	<b>11</b>
<b>9.2.2</b>	<b>Operation .....</b>	<b>11</b>
<b>9.2.3</b>	<b>Slippage .....</b>	<b>11</b>
<b>9.2.4</b>	<b>Jaw breaks .....</b>	<b>11</b>
<b>9.2.5</b>	<b>Test on wet test pieces .....</b>	<b>11</b>
<b>9.3</b>	<b>Calculation and expression of results .....</b>	<b>13</b>
<b>9.4</b>	<b>Test report .....</b>	<b>13</b>