

# ISO 6179:2017-07 (E)

## Rubber, vulcanized or thermoplastic - Rubber sheets and rubber-coated fabrics - Determination of transmission rate of volatile liquids (gravimetric technique)

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Apparatus .....</b>	<b>2</b>
<b>5</b>	<b>Calibration .....</b>	<b>2</b>
<b>6</b>	<b>Test pieces .....</b>	<b>2</b>
<b>6.1</b>	<b>Preparation .....</b>	<b>2</b>
<b>6.2</b>	<b>Thickness measurement .....</b>	<b>3</b>
<b>6.3</b>	<b>Number of test pieces .....</b>	<b>3</b>
<b>7</b>	<b>Time-interval between vulcanization and testing .....</b>	<b>4</b>
<b>8</b>	<b>Conditioning .....</b>	<b>4</b>
<b>9</b>	<b>Test conditions .....</b>	<b>4</b>
<b>9.1</b>	<b>Temperature .....</b>	<b>4</b>
<b>9.2</b>	<b>Duration of test .....</b>	<b>4</b>
<b>10</b>	<b>Procedure .....</b>	<b>5</b>
<b>10.1</b>	<b>Preliminary operations .....</b>	<b>5</b>
<b>10.2</b>	<b>Method A .....</b>	<b>5</b>
<b>10.3</b>	<b>Method B .....</b>	<b>5</b>
<b>11</b>	<b>Expression of results .....</b>	<b>6</b>
<b>11.1</b>	<b>Method of calculation .....</b>	<b>6</b>
<b>11.2</b>	<b>Graphical method .....</b>	<b>6</b>
<b>12</b>	<b>Test report .....</b>	<b>6</b>
<b>Annex A (normative) Calibration schedule .....</b>		<b>7</b>
<b>Bibliography .....</b>		<b>9</b>