

DIN EN 15860:2018-09 (E)

Plastics - Thermoplastic semi-finished products for machining - Requirements and test methods

| Contents | | Page |
|-------------------------|---|-------------|
| European foreword | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 6 |
| 4 | Materials | 6 |
| 5 | Requirements | 7 |
| 5.1 | As-delivered condition | 7 |
| 5.2 | Surface appearance | 8 |
| 5.3 | Dimensions and tolerances for rods | 8 |
| 5.3.1 | Diameter | 8 |
| 5.3.2 | Length | 11 |
| 5.3.3 | Roundness | 11 |
| 5.3.4 | Straightness | 12 |
| 5.4 | Dimensions and tolerances for hollow bars | 13 |
| 5.4.1 | Diameters | 13 |
| 5.4.2 | Length | 15 |
| 5.4.3 | Roundness | 15 |
| 5.4.4 | Straightness | 15 |
| 5.4.5 | Concentricity | 16 |
| 5.5 | Dimensions and tolerances for sheets | 17 |
| 5.5.1 | Thickness | 17 |
| 5.5.2 | Length and width | 18 |
| 5.5.3 | Straightness | 19 |
| 5.6 | Properties | 22 |
| 5.6.1 | Material properties | 22 |
| 5.6.2 | Dimensional stability after heat treatment | 22 |
| 5.6.3 | Physiological behaviour | 24 |
| 6 | Test methods | 24 |
| 6.1 | Test conditions | 24 |
| 6.2 | Sampling size | 24 |
| 6.3 | Test specimen preparation | 24 |
| 6.3.1 | Mechanical properties | 24 |
| 6.3.2 | Density | 26 |
| 6.3.3 | Melt volume-flow rate, viscosity number, melting temperature/glass transition temperature | 26 |
| 6.3.4 | Dimensional stability after heat treatment | 26 |
| 6.4 | As-delivered condition | 27 |
| 6.5 | Surface appearance | 27 |
| 6.6 | Accuracy of the dimension measuring instruments | 27 |
| 6.7 | Density | 27 |
| 6.8 | Tensile stress at yield and elongation at break | 28 |
| 6.9 | Tensile modulus of elasticity | 28 |
| 6.10 | Vicat softening temperature | 28 |
| 6.11 | Melt volume-flow rate (MVR) | 28 |
| 6.12 | Melting temperature/glass transition temperature | 29 |

| | | |
|---|--|----|
| 6.13 | Viscosity number | 29 |
| 6.14 | Dimensional stability after heat treatment | 29 |
| 6.15 | Expression of test results | 33 |
| 7 | Designation | 33 |
| 7.1 | Rods | 33 |
| 7.2 | Hollow bars | 33 |
| 7.3 | Sheets | 34 |
| 8 | Marking | 34 |
| Annex A (normative) Determination of microporosity - Dye penetration method | | 35 |
| A.1 | Test specimen preparation | 35 |
| A.2 | Test procedure | 35 |
| A.3 | Test results | 35 |
| Annex B (normative) Tables for the conversion of deflection values (straightness) | | 37 |
| Annex C (informative) Examples of calculation of dimensional stability after heat treatment | | 41 |
| C.1 | Rods | 41 |
| C.2 | Hollow bars | 41 |
| C.3 | Sheets | 42 |
| Annex D (informative) Some guideline values for material properties of thermoplastic semi-finished products | | 44 |
| Bibliography | | 48 |