

# DIN 16961-2:2018-08 (E)

## Thermoplastics pipes and fittings with profiled wall and smooth pipe inside - Part 2: Technical delivery specifications

---

<b>Contents</b>	<b>Page</b>
<b>Foreword</b> .....	<b>3</b>
<b>1 Scope</b> .....	<b>4</b>
<b>2 Normative references</b> .....	<b>4</b>
<b>3 Material (moulding material)</b> .....	<b>5</b>
<b>4 Requirements</b> .....	<b>6</b>
<b>4.1 General requirements</b> .....	<b>6</b>
<b>4.2 Mechanical and physical characteristics</b> .....	<b>7</b>
<b>5 Testing</b> .....	<b>10</b>
<b>5.1 General tests</b> .....	<b>10</b>
<b>5.2 Testing of mechanical and physical characteristics</b> .....	<b>10</b>
<b>6 Scope of testing</b> .....	<b>15</b>
<b>7 Marking</b> .....	<b>18</b>
<b>Annex A (informative) Calculating <math>S_{R24}</math> ring stiffness for a solid wall cross-section (Example)</b> .....	<b>19</b>
<b>A.1 Schematic test set-up and measured values</b> .....	<b>19</b>
<b>A.2 Calculation steps</b> .....	<b>19</b>
<b>Annex B (informativ) Long-term hydrostatic strength test</b> .....	<b>23</b>
<b>Annex C (normative) Reference curves for selected materials</b> .....	<b>25</b>
<b>C.1 PE 80</b> .....	<b>25</b>
<b>C.2 PE 100</b> .....	<b>26</b>
<b>C.3 PP-H</b> .....	<b>27</b>
<b>C.4 PP-B</b> .....	<b>28</b>
<b>C.5 PP-R</b> .....	<b>29</b>
<b>Annex D (normative) Minimum wall thickness for pipes sized according to internal diameter</b> .....	<b>30</b>
<b>D.1 Polyethylene (PE 80 and PE 100)</b> .....	<b>30</b>
<b>D.2 Polypropylene (PP-H and PP-R)</b> .....	<b>32</b>
<b>Annex E (normative) Durability of profiled pipes in applications without pressure</b> .....	<b>34</b>
<b>Bibliography</b> .....	<b>35</b>