

# DIN 16961-2:2018-08 (E)

## Thermoplastics pipes and fittings with profiled wall and smooth pipe inside - Part 2: Technical delivery specifications

---

<b>Contents</b>	<b>Page</b>
<b>Foreword</b> .....	<b>3</b>
<b>1 Scope</b> .....	<b>4</b>
<b>2 Normative references</b> .....	<b>4</b>
<b>3 Material (moulding material)</b> .....	<b>5</b>
<b>4 Requirements</b> .....	<b>6</b>
4.1 General requirements.....	6
4.2 Mechanical and physical characteristics .....	7
<b>5 Testing</b> .....	<b>10</b>
5.1 General tests.....	10
5.2 Testing of mechanical and physical characteristics .....	10
<b>6 Scope of testing</b> .....	<b>15</b>
<b>7 Marking</b> .....	<b>18</b>
<b>Annex A (informative) Calculating <math>S_{R24}</math> ring stiffness for a solid wall cross-section (Example)</b> .....	<b>19</b>
A.1 Schematic test set-up and measured values.....	19
A.2 Calculation steps.....	19
<b>Annex B (informativ) Long-term hydrostatic strength test</b> .....	<b>23</b>
<b>Annex C (normative) Reference curves for selected materials</b> .....	<b>25</b>
C.1 PE 80.....	25
C.2 PE 100 .....	26
C.3 PP-H .....	27
C.4 PP-B .....	28
C.5 PP-R .....	29
<b>Annex D (normative) Minimum wall thickness for pipes sized according to internal diameter</b> .....	<b>30</b>
D.1 Polyethylene (PE 80 and PE 100) .....	30
D.2 Polypropylene (PP-H and PP-R).....	32
<b>Annex E (normative) Durability of profiled pipes in applications without pressure</b> .....	<b>34</b>
<b>Bibliography</b> .....	<b>35</b>