

DIN 16873:2018-09 (E)

Pipes and fittings of unplasticized poly(vinyl chloride) (PVC-U) for cable ducting - Dimensions and technical delivery conditions

Contents		Page
Foreword		4
1 Scope		5
2 Normative references		5
3 Terms and definitions		6
4 Symbols and abbreviations		7
4.1 Symbols		7
4.2 Abbreviations		7
5 Dimensions, designation		8
5.1 General		8
5.2 Pipes		8
5.2.1 General		8
5.2.2 Pipe outside diameters and wall thicknesses		8
5.3 Fittings		10
6 Material		10
6.1 Pipes and fittings		10
6.2 Seals		10
6.3 Adhesives		10
7 Requirements		10
7.1 General		10
7.2 Appearance		10
7.3 Colour		11
7.4 Dimensions and tolerances		11
7.5 Strength properties		11
7.5.1 Long-term hydrostatic strength		11
7.5.2 Resistance to external blows		11
7.6 Heat reversion		12
7.7 Vicat softening temperature		12
8 Testing		12
8.1 Appearance		12
8.2 Colour		12
8.3 Dimensions		12
8.4 Strength properties		13
8.4.1 Long-term hydrostatic strength		13
8.4.2 Resistance to external blows		13
8.5 Heat reversion		13
8.6 Vicat softening temperature		13
9 Marking		13
9.1 General		13
9.2 Minimum marking of pipes		14
10 Laying instructions		14
10.1 Structural strength		14

10.2	Installation of pipes and fittings.....	14
Annex A	(normative) Fittings for straight pipes.....	15
A.1	Dimensions.....	15
A.2	Requirements.....	20
A.3	Testing of injection-moulded fittings.....	21
A.4	Additional marking.....	21
Annex B	(informative) Terms which are not used in this standard, but are of relevance for the user.....	22
Bibliography	23