

DIN 16873:2018-09 (E)

Pipes and fittings of unplasticized poly(vinyl chloride) (PVC-U) for cable ducting - Dimensions and technical delivery conditions

Contents		Page
Foreword		4
1	Scope	5
2	Normative references	5
3	Terms and definitions.....	6
4	Symbols and abbreviations.....	7
4.1	Symbols	7
4.2	Abbreviations	7
5	Dimensions, designation.....	8
5.1	General	8
5.2	Pipes	8
5.2.1	General	8
5.2.2	Pipe outside diameters and wall thicknesses	8
5.3	Fittings	10
6	Material	10
6.1	Pipes and fittings.....	10
6.2	Seals.....	10
6.3	Adhesives	10
7	Requirements	10
7.1	General	10
7.2	Appearance	10
7.3	Colour.....	11
7.4	Dimensions and tolerances.....	11
7.5	Strength properties	11
7.5.1	Long-term hydrostatic strength	11
7.5.2	Resistance to external blows	11
7.6	Heat reversion.....	12
7.7	Vicat softening temperature.....	12
8	Testing	12
8.1	Appearance	12
8.2	Colour.....	12
8.3	Dimensions.....	12
8.4	Strength properties	13
8.4.1	Long-term hydrostatic strength	13
8.4.2	Resistance to external blows	13
8.5	Heat reversion.....	13
8.6	Vicat softening temperature.....	13
9	Marking	13
9.1	General	13
9.2	Minimum marking of pipes.....	14
10	Laying instructions.....	14
10.1	Structural strength	14

10.2	Installation of pipes and fittings	14
Annex A	(normative) Fittings for straight pipes	15
A.1	Dimensions	15
A.2	Requirements	20
A.3	Testing of injection-moulded fittings	21
A.4	Additional marking	21
Annex B	(informative) Terms which are not used in this standard, but are of relevance for the user	22
Bibliography	23