

# ISO 7432:2018 (E)

## Glass-reinforced thermosetting plastics (GRP) pipes and fittings — Test methods to prove the design of locked socket-and-spigot joints, including double-socket joints, with elastomeric seals

---

### Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Principle
5	Apparatus
5.1	End-sealing devices
5.2	Supports
5.3	Source of hydrostatic pressure
5.4	Pressure gauges
5.5	Vacuum pump
5.6	Means of applying and measuring the required deformation and bending forces
6	Test pieces
6.1	Assembly and test arrangement
6.2	Number of test pieces
7	Conditioning
8	Test temperature
9	Procedure
9.1	General
9.2	Negative pressure
9.3	Deformation with internal pressure and end thrust
9.4	Deformation with cyclic pressure and end thrust
9.5	Bending with cyclic pressure and end thrust
9.6	Internal pressure and end thrust
10	Test report
Annex A	(normative) Calculation of the bending load F <sub>2</sub> used in the bending test in 9.5
A.1	General
A.2	Calculation of F <sub>2</sub> , if applied in the horizontal plane
A.3	Calculation of F <sub>2</sub> , if applied in the vertical plane

Page count: 12