

# ISO 11299-2:2018 (E)

## Plastics piping systems for renovation of underground gas supply networks — Part 2: Lining with continuous pipes

---

### Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols and abbreviated terms
4.1	Symbols
4.2	Abbreviated terms
5	Pipes at the “M” stage
5.1	Materials
5.2	General characteristics
5.3	Material characteristics
5.4	Geometrical characteristics
5.5	Mechanical characteristics
5.6	Physical characteristics
5.7	Joining
5.8	Marking
5.9	Regional requirements for pipes
6	Fittings at the “M” stage
6.1	Requirement for fittings
6.2	Marking
6.3	Regional requirements for fittings
7	Ancillary components
8	Fitness for purpose of the installed lining system at the “I” stage
9	Installation practice
9.1	Preparatory work
9.2	Storage, handling and transport
9.3	Equipment
9.3.1	Butt fusion equipment and debanding equipment
9.3.2	Pipe rollers
9.3.3	Winching and rod-pulling equipment
9.3.4	Pipe entry guides
9.3.5	Electrofusion equipment
9.3.6	Inspection equipment
9.3.7	Lifting equipment
9.4	Installation
9.5	Process-related inspection and testing
9.6	Lining termination
9.7	Reconnections to the existing pipeline system
9.8	Final inspection and testing
9.9	Documentation
Annex A	(normative) Layered pipes
A.1	General
A.2	Pipes with co-extruded layers
A.3	Coated pipe