

# ISO 6721-5:2019 (E)

## Plastics — Determination of dynamic mechanical properties — Part 5: Flexural vibration — Non-resonance method

---

### Contents

|        |   |
|--------|---|
|        | Foreword  |
| 1      | Scope   |
| 2      | Normative references                                      |
| 3      | Terms and definitions                                     |
| 4      | Principle   |
| 5      | Apparatus   |
| 5.1    | Loading assembly  |
| 5.1.1  | General   |
| 5.1.2  | Load stage  |
| 5.1.3  | Transducers   |
| 5.2    | Electronic data-processing equipment                      |
| 5.3    | Temperature measurement and control                       |
| 5.4    | Devices for measuring test specimen dimensions            |
| 6      | Test specimens  |
| 6.1    | General   |
| 6.2    | Shape and dimensions                                      |
| 6.3    | Preparation   |
| 7      | Number of specimens                                       |
| 8      | Conditioning  |
| 9      | Procedure   |
| 9.1    | Test atmosphere   |
| 9.2    | Measuring the cross-section of the specimen               |
| 9.3    | Clamping the specimen                                     |
| 9.4    | Varying the temperature                                   |
| 9.5    | Performing the test                                       |
| 10     | Expression of results                                     |
| 10.1   | Symbols   |
| 10.2   | Calculation of flexural storage modulus $E_f'$            |
| 10.2.1 | General   |
| 10.2.2 | Avoidance of specimen resonance                           |
| 10.2.3 | Correction for transducer resonance                       |
| 10.2.4 | Correction for apparatus compliance                       |
| 10.2.5 | Application of a length correction                        |
| 10.3   | Calculation of the flexural loss factor $\tan \delta E_f$ |
| 10.4   | Calculation of the flexural loss modulus $E_f''$          |
| 10.5   | Presentation of data as a function of temperature         |
| 11     | Precision   |
| 12     | Test report   |