## ISO 307:2019 (E)

## Plastics — Polyamides — Determination of viscosity number

## Contents

Foreword Introduction

- 1 Scope
- 2 Normative references
- 3 Terms and definitions
- 4 Principle
- 5 Reagents and materials
  - 5.1 Solvents and reagents
  - 5.2 Cleaning liquids
- 6 Apparatus
- 7 Preparation of test samples
  - 7.1 General
  - 7.2 Samples containing less than 98 % (by mass) polyamide
- 8 Calculation of test portion
- 9 Selection of solvent
- 10 Procedure
  - 10.1 Cleaning of the viscometer
  - 10.2 Preparation of test solution
  - 10.2.1 General
  - 10.2.2 Volumetric method
  - 10.2.3 Volumetric method, in exact relation to the polymer content
  - 10.2.4 Gravimetric method, in exact relation to the polymer content
  - 10.3 Measurement of flow times
- 11 Expression of results
- 12 Repeatability and reproducibility
- 13 Relationship between the viscosity number determined in 96 % (by mass) sulfuric acid solution and the viscosity determined in various solvents
- 14 Test report
- Annex A (informative) Determination of the concentration of commercial sulfuric acid(95 % to 98 %) and adjustment to 96 % by titration
  - A.1 General
  - A.2 Apparatus and reagents
  - A.3 Procedure
  - A.3.1 Check on the titre of hydrochloric acid
  - A.3.2 Preparation of sodium hydroxide solution, 1 mol/l
  - A.3.3 Determination of the titre of sodium hydroxide solution
  - A.3.4 Determination of the titre of initial sulfuric acid solution
  - A.4 Expression of results

- A.5 Adjustment of sulfuric acid concentration
- A.5.1 Concentration of sulfuric acid solution lower than 96 %
- A.5.2 Concentration of sulfuric acid solution higher than 96 %
- Annex B (informative) Determination of the concentration of sulfuric acid (95 % to 98 %) and adjustment to 96 % by flow time measurement in a small capillary viscometer
  - B.1 General
  - B.2 Apparatus
  - B.3 Preparation of calibration curve
  - B.4 Adjustment of sulfuric acid concentration
  - B.4.1 Concentration of sulfuric acid solution lower than 96 %
  - B.4.2 Concentration of sulfuric acid solution higher than 96 %
- Annex C (informative) Determination of the concentration of commercial formic acid and adjustment to 90 % by titration
  - C.1 General
  - C.2 Apparatus and reagents
  - C.3 Procedure
  - C.3.1 Determination of the titre of the sodium hydroxide solution
  - C.3.2 Determination of the formic acid concentration
  - C.4 Adjustment of formic acid concentration
- Annex D (informative) Determination of the concentration of commercial formic acid and adjustment to 90 % by density measurement
  - D.1 General
  - D.2 Apparatus
  - D.3 Procedure
- Annex E (informative) Relationship between the viscosity number determined in 96 % (by mass) sulfuric acid solution and the viscosity determined in various solvents
  - E.1 Relationship between the viscosity numbers determined in 96 % (by mass) sulfuric acid, 90 % (by mass) formic acid and m#cresol
  - E.1.1 Viscosity numbers in 96 % (by mass) sulfuric acid and 90 % (by mass) formic acid, respectively
  - E.1.2 Viscosity numbers in 96 % (by mass) sulfuric acid and m#cresol, respectively
  - E.1.3 Precision
  - E.2 Relative viscosities determined in accordance with ASTM D789 and viscosity numbers determined in 96 % (by mass) sulfuric acid
  - E.3 Interconversion of relative viscosity (JIS K 6920-2:2009, Annex JA) and viscosity number for PA 6 and PA 66 (this document)
  - E.4 Interconversion of relative viscosity in 95,7 % (by mass) sulfuric acid at a concentration of 0,01 g/ml and viscosity number for PA 6 and PA 66 (this document)

Page count: 35