

ISO 22838:2020 (E)

Composites and reinforcements fibres — Determination of the fracture energy of bonded plates of carbon fibre reinforced plastics (CFRPs) and metal using double cantilever beam specimens

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms, definitions and symbols
3.1	Terms and definitions
3.2	Symbols
4	Principle
5	Apparatus
6	Specimens
6.1	Number of specimens
6.2	Conditioning
6.3	Manufacture of adhesive joint specimens
6.3.1	General
6.3.2	DCB specimen measurements
6.4	Preparation of specimens
7	Procedure
7.1	Test set-up and data recording
7.2	Initial loading (precracking stage)
7.3	Re-loading: Testing from the precrack
7.4	Determination of the thickness ratio of the CFRP and metal beams
7.4.1	Theoretical prediction of thickness ratios
7.4.2	Procedure to detect the occurrence of plastic deformation during a DCB adhesive joint test
7.5	Measurement of machine compliance
7.6	Measurement of curvature induced by coefficient of thermal expansion difference between metal and composite beams
8	Data analysis
8.1	Determination of the raw data from the load-displacement trace
8.1.1	General
8.1.2	Initiation values
8.1.3	Propagation values
8.2	Determination of adhesive fracture energy
8.2.1	General
8.2.2	DCB test with identical thickness: Corrected beam theory (CBT)
8.2.3	DCB test with dissimilar thicknesses: modified beam theory for DCB specimens with dissimilar thicknesses
8.2.4	DCB test with identical and dissimilar thicknesses: Area method
9	Precision
10	Test report

Annex A (informative) Work flow chart as brief guideline

Annex B (informative) Formula for calculating G value using (E)eq or E111 E212

Annex C (normative) Measurement of test system compliance

Page count: 22