ISO 11443:2021-02 (E)

Plastics - Determination of the fluidity of plastics using capillary and slit-die rheometers

Contents

Page

Foreword v

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 General principles 4

5 Apparatus 4
5.1 Test device 4
5.1.1 General 4
5.1.2 Rheometer barrel 5
5.1.3 Capillary dies (method A) 5
5.1.4 Slit dies (method B) 9
5.1.5 Piston 9
5.2 Temperature control 9
5.3 Measurement of temperature and calibration 10
5.3.1 Test temperature 10
5.3.2 Measurement of test temperature 10
5.3.3 Temperature calibration 10
5.4 Measurement of pressure and calibration 10
5.4.1 Test pressure 10
5.4.2 Pressure drop along the length of the slit die 11
5.4.3 Calibration 11
5.5 Measurement of the volume flow rate of the sample 11

6 Sampling 11

7 Procedure 11
7.1 Cleaning the test device 11
7.2 Selection of test temperatures 12
7.3 Preparation of samples 13
7.4 Preheating 13
7.5 Determination of the maximum permissible test duration 13
7.6 Determination of test pressure at constant volume flow rate: Method 2 14
7.7 Determination of volume flow rate at constant test pressure: Method 1 14
7.8 Waiting periods during measurement 14
7.9 Measurement of extrudate swelling 14
7.9.1 General 14
7.9.2 Measurement at room temperature 15
7.9.3 Measurement at the test temperature 15

8 Expression of results 15
8.1 Volume flow rate 15
8.2 Apparent shear rate 16
8.2.1 General 16
8.2.2 Method A: Capillary dies 16
8.2.3 Method B: Slit dies 16
8.3 Apparent shear stress 17

8.3.1 General 17
8.3.2 Method A: Capillary dies 17
8.3.3 Method B: Slit dies 17
8.4 True shear stress 17
8.4.1 General 17
8.4.2 Bagley correction for capillary dies (method A) 18
8.4.3 Bagley correction for slit dies (method B) 21
8.4.4 Direct determination using slit dies (method B) 22
8.5 True shear rate 22
8.5.1 General 22
8.5.2 Method A: Capillary dies 23
8.5.3 Method B: Slit dies 23
8.6 Viscosity 23
8.7 Determination of extrudate swelling 23
8.7.1 Measurement at room temperature 23
8.7.2 Measurement at the test temperature 24

9 Precision 24

10 Test report 25
10.1 General 25
10.2 Test conditions 25
10.3 Flow characteristics 26
10.3.1 General 26
10.3.2 Graphical representation 26
10.3.3 Individual values 27
10.4 Visual examination 27

Annex A (informative) Method of correcting for the influence of H/B on the apparent shear rate.28
Annex B (informative) Measurement errors 30

Annex C (informative) Uncertainties in the determination of shear viscosity by capillary extrusion rheometry testing 31

Bibliography 36