

# ISO 7432:2021-04 (E)

## Glass-reinforced thermosetting plastics (GRP) pipes and fittings - Test methods to prove the design of locked socket-and-spigot joints, including double-socket joints, with elastomeric seals

---

| Contents                   |   | Page      |
|----------------------------|---|-----------|
| Foreword                   |   | iv        |
| Introduction               |   | v         |
| <b>1</b>                   | <b>Scope</b>  | <b>1</b>  |
| <b>2</b>                   | <b>Normative references</b>   | <b>1</b>  |
| <b>3</b>                   | <b>Terms and definitions</b>  | <b>1</b>  |
| <b>4</b>                   | <b>Principle</b>  | <b>2</b>  |
| <b>5</b>                   | <b>Apparatus</b>  | <b>3</b>  |
| 5.1                        | End-sealing devices   | 3         |
| 5.2                        | Supports  | 3         |
| 5.3                        | Source of hydrostatic pressure  | 3         |
| 5.4                        | Pressure gauges   | 3         |
| 5.5                        | Vacuum pump   | 3         |
| 5.6                        | Means of applying and measuring the required deformation and bending forces   | 3         |
| <b>6</b>                   | <b>Test pieces</b>  | <b>4</b>  |
| 6.1                        | General   | 4         |
| 6.2                        | Test arrangement for tests detailed in <a href="#">9.2</a> and <a href="#">9.6</a>  | 4         |
| 6.3                        | Test arrangement for tests detailed in <a href="#">9.3</a> and <a href="#">9.4</a>  | 4         |
| 6.4                        | Test arrangement for tests detailed in <a href="#">9.5</a>  | 5         |
| 6.5                        | Number of test pieces   | 7         |
| <b>7</b>                   | <b>Conditioning</b>   | <b>7</b>  |
| <b>8</b>                   | <b>Test temperature</b>   | <b>7</b>  |
| <b>9</b>                   | <b>Procedure</b>  | <b>7</b>  |
| 9.1                        | General   | 7         |
| 9.2                        | Negative pressure   | 8         |
| 9.3                        | Deformation with internal pressure and end thrust   | 9         |
| 9.4                        | Deformation with cyclic pressure and end thrust   | 9         |
| 9.5                        | Bending with cyclic pressure and end thrust   | 9         |
| 9.5.1                      | Introductory notes  | 9         |
| 9.5.2                      | Method A  | 10        |
| 9.5.3                      | Method B  | 10        |
| 9.6                        | Internal pressure and end thrust  | 11        |
| <b>10</b>                  | <b>Test report</b>  | <b>11</b> |
| <b>Annex A</b> (normative) | <b>Calculation of the additional force, <math>F_A</math>, and limiting deflection, <math>\Delta</math>, used in <a href="#">9.5</a>, Method A</b> | <b>13</b> |
| <b>Annex B</b> (normative) | <b>Calculation of the bending load, <math>F_B</math>, used in the bending test in <a href="#">9.5</a>, Method B</b>                               | <b>14</b> |