DIN EN ISO 16486-4:2022-06 (E)

Plastics piping systems for the supply of gaseous fuels - Unplasticized polyamide (PA-U) piping systems with fusion jointing and mechanical jointing - Part 4: Valves (ISO 16486-4:2022)

Contents

Page

European foreword ... **4**

Annex (informative) **A-deviation** ... **5**

Foreword ... **6**

Introduction ... **8**

1 Scope ... **9**

2 Normative references ... **9**

3 Terms and definitions ... **10**
3.1 General ... 11
3.2 Terms relating to design ... 11

4 Symbols and abbreviated terms ... **11**

5 Material ... **12**
5.1 Compound for valve body ... 12
5.1.1 Compound ... 12
5.1.2 Fusion compatibility ... 12
5.2 Material for non-polyamide parts ... 12
5.2.1 General ... 12
5.2.2 Metal parts ... 12
5.2.3 Elastomers ... 13
5.2.4 Greases and lubricants ... 13
5.2.5 Assembly ... 13

6 General characteristics ... **13**
6.1 Appearance of the valve ... 13
6.2 Colour ... 13
6.3 Design ... 13
6.3.1 General ... 13
6.3.2 Valve body ... 13
6.3.3 Valve terminal ends ... 13
6.3.4 Operating device ... 13
6.3.5 Seals ... 14

7 Geometrical characteristics ... **14**
7.1 General ... 14
7.2 Measurement of dimensions ... 14
7.3 Dimensions of spigot ends for valves ... 14
7.4 Dimensions of valves with electrofusion sockets ... 14
7.5 Dimensions of the operating device ... 14

8 Mechanical characteristics of assembled valves and regional requirements ... **15**
8.1 General ... 15
8.2 Conditioning ... 15
8.3 Requirements ... 15
8.3.1 Generals ... 15
8.3.2 Air flow rate ... 20
8.4 Regional requirement ... 20

9 Physical characteristics **21**
9.1 Conditioning 21
9.2 Requirement 21
10 Performance requirements **21**
11 Technical File **21**
12 Marking **22**
12.1 General 22
12.2 Minimum required marking of valves 22
12.3 Additional marking 23
13 Delivery Conditions **23**
Annex A (normative) **Determination of the leaktightness of seat(s) and packing** **24**
Annex B (normative) **Test method for leaktightness and ease of operation after tensile loading** **26**
Bibliography **28**