

ISO 16486-4:2022-01 (E)

Plastics piping systems for the supply of gaseous fuels - Unplasticized polyamide (PA-U) piping systems with fusion jointing and mechanical jointing - Part 4: Valves

Contents		Page
Foreword		v
Introduction		vii
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
3.1	General	3
3.2	Terms relating to design	3
4	Symbols and abbreviated terms	3
5	Material	4
5.1	Compound for valve body	4
5.1.1	Compound	4
5.1.2	Fusion compatibility	4
5.2	Material for non-polyamide parts	4
5.2.1	General	4
5.2.2	Metal parts	4
5.2.3	Elastomers	5
5.2.4	Greases and lubricants	5
5.2.5	Assembly	5
6	General characteristics	5
6.1	Appearance of the valve	5
6.2	Colour	5
6.3	Design	5
6.3.1	General	5
6.3.2	Valve body	5
6.3.3	Valve terminal ends	5
6.3.4	Operating device	5
6.3.5	Seals	6
7	Geometrical characteristics	6
7.1	General	6
7.2	Measurement of dimensions	6
7.3	Dimensions of spigot ends for valves	6
7.4	Dimensions of valves with electrofusion sockets	6
7.5	Dimensions of the operating device	6
8	Mechanical characteristics of assembled valves and regional requirements	7
8.1	General	7
8.2	Conditioning	7
8.3	Requirements	7
8.3.1	Generals	7
8.3.2	Air flow rate	12
8.4	Regional requirement	12
9	Physical characteristics	13

9.1	Conditioning	13
9.2	Requirement	13
10	Performance requirements	13
11	Technical File	13
12	Marking	14
12.1	General	14
12.2	Minimum required marking of valves	14
12.3	Additional marking	15
ISO 16486-4:2022(E) ISO 16486-4:2022(E) 13 Delivery Conditions		15
Annex A (normative) Determination of the leaktightness of seat(s) and packing		16
Annex B (normative) Test method for leaktightness and ease of operation after tensile loading		18
Bibliography		20