

ISO/TS 23483:2022-08 (E)

Carbon fibres - Determination of polyacrylonitrile-based (PAN-based) carbon fibre tow characteristics - Heat transfer parameter

| Contents | | Page |
|--|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 Scope | | 1 |
| 2 Normative references | | 1 |
| 3 Terms and definitions | | 1 |
| 4 Principle | | 1 |
| 5 Test devices | | 2 |
| 6 Test conditions on carbon fibre tow | | 3 |
| 7 Traceability – Calibration | | 3 |
| 8 Test procedures | | 3 |
| 8.1 Type | | 3 |
| 8.2 Size | | 3 |
| 8.3 Thermal imaging camera | | 3 |
| 8.3.1 Working parameters of thermal imaging camera | | 3 |
| 8.4 Thermal imaging camera scan range on a sample | | 3 |
| 8.5 Sample preparations | | 4 |
| 8.5.1 Mounting and handling | | 4 |
| 8.6 No. of samples and no. of measurements | | 4 |
| 8.7 Data | | 4 |
| 9 Test report | | 5 |
| Annex A (informative) Typical set-up for heat transfer parameter measurement | | 6 |
| Annex B (informative) Determination of 12 K carbon fibre tow heat transfer parameter | | 9 |
| Bibliography | | 10 |