

# ISO 22007-7:2023-04 (E)

## Plastics - Determination of thermal conductivity and thermal diffusivity - Part 7: Transient measurement of thermal effusivity using a plane heat source

---

<b>Contents</b>	<b>Page</b>
<b>Foreword</b> .....	<b>iv</b>
<b>Introduction</b> .....	<b>v</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Principle</b> .....	<b>2</b>
<b>5 Apparatus</b> .....	<b>2</b>
<b>6 Test specimens</b> .....	<b>2</b>
6.1 Configuration A: Rod-shaped specimens having a thermal effusivity above 1 000 W·s <sup>1/2</sup> ·m <sup>-2</sup> ·K <sup>-1</sup> .....	2
6.2 Configuration B: Specimens of thermal effusivity below 1 000 W·s <sup>1/2</sup> ·m <sup>-2</sup> ·K <sup>-1</sup> completely embedding the probe.....	3
6.3 Specimen preparation.....	3
<b>7 Procedure</b> .....	<b>4</b>
<b>8 Calculation of thermal effusivity</b> .....	<b>6</b>
8.1 Computations.....	6
8.2 Single-sided setup.....	9
<b>9 Verification procedures</b> .....	<b>9</b>
9.1 Calibration of apparatus.....	9
9.2 Verification of apparatus.....	9
<b>10 Precision and bias</b> .....	<b>10</b>
<b>11 Test report</b> .....	<b>10</b>
<b>Annex A (informative) Example of testing a homogeneous, anisotropic rod</b> .....	<b>11</b>
<b>Annex B (informative) Example of testing a stacked, anisotropic Rod</b> .....	<b>14</b>
<b>Bibliography</b> .....	<b>16</b>