ISO 16486-6:2023-10 (E)

Plastics piping systems for the supply of gaseous fuels - Unplasticized polyamide (PA-U) piping systems with fusion jointing and mechanical jointing - Part 6: Code of practice for design, handling and installation

Contents

Page

Foreword ..... **v**

Introduction ..... **vii**

1 Scope **1**

2 Normative references **1**

3 Terms, definitions and abbreviated terms **2**
3.1 Terms and definitions 2
3.2 Symbols and abbreviated terms 3

4 Design **4**
4.1 General and regional requirements 4
4.1.1 General 4
4.1.2 Regional requirements 4
4.2 Materials, components and jointing equipment 5
4.3 Maximum operating pressure 5
4.3.1 General 5
4.3.2 Maximum operation pressure based on long-term hydrostatic strength 5
4.3.3 Maximum operation pressure based on rapid crack propagation 5
4.4 Assembly techniques 6
4.5 Squeeze-off properties 6

5 Construction **7**
5.1 Competence 7
5.2 Storage, handling and transport 7
5.2.1 General 7
5.2.2 Storage 7
5.2.3 Handling 8
5.2.4 Transport 9
5.3 Jointing 9
5.4 Laying 9
5.4.1 General 9
5.4.2 Trench 10
5.4.3 Drag forces 10
5.4.4 Valves 11
5.4.5 Connection to existing systems 11
5.4.6 Backfilling 11
5.4.7 Non-conventional installation 12
5.5 Pressure testing and commissioning 12

6 Quality control **12**
6.1 General 12
6.2 Inspection prior to laying 12
6.3 Inspection during laying 13
6.3.1 Laying 13
6.3.2 Joint integrity 13

Annex A (normative) **Butt fusion jointing procedure** **20**

Annex B (normative) **Electrofusion jointing** **25**

Annex C (normative) **Mechanical jointing** **31**

Annex D (informative) **Squeeze-off and re-rounding** **32**

Annex E (normative) **Derating coefficients for various operating temperatures** **35**
Annex F (informative) **Regional requirements for CEN member countries** **36**
Annex G (informative) **Additional information for demonstrating the fitness of PA-U piping systems for non-conventional installation techniques** **37**
Bibliography **39**