

# ISO 16422-2:2024-02 (E)

## Pipes and joints made of oriented unplasticized poly(vinyl chloride ) (PVC-O) for the conveyance of water under pressure - Part 2: Pipes

---

### Contents

Page

Foreword.....	iv
Introduction.....	v
<b>1 Scope.....</b>	<b>1</b>
<b>2 Normative references.....</b>	<b>1</b>
<b>3 Terms and definitions.....</b>	<b>2</b>
<b>4 Symbols.....</b>	<b>4</b>
<b>5 Material.....</b>	<b>5</b>
5.1 General.....	5
5.2 Density.....	5
5.3 MRS class.....	6
5.4 Orientation factor.....	6
<b>6 General characteristics.....</b>	<b>6</b>
6.1 Appearance.....	6
6.2 Colour.....	6
6.3 Opacity.....	6
6.4 Classification of pipes.....	7
6.4.1 Classification.....	7
6.4.2 Calculation of wall thickness.....	7
<b>7 Geometrical characteristics.....</b>	<b>7</b>
7.1 Measurement of dimensions.....	7
7.2 Length of pipes.....	7
7.3 Nominal outside diameters and wall thicknesses.....	7
7.4 Pipes with integral sockets with elastomeric sealing ring type.....	9
7.5 Plain ends.....	11
<b>8 Selection of pipes.....</b>	<b>11</b>
8.1 Selection of nominal pressure and pipe series S for water up to and including 25 °C.....	11
8.2 Determination of the allowable operating pressure for water up to 45 °C.....	11
<b>9 Mechanical characteristics.....</b>	<b>11</b>
9.1 Resistance to hydrostatic pressure.....	11
9.1.1 General.....	11
9.1.2 Pipes.....	12
9.1.3 Pipes with integral sockets.....	12
9.2 Impact strength.....	12
9.3 Ring stiffness.....	13
<b>10 Physical characteristics.....</b>	<b>13</b>
<b>11 Sealing rings.....</b>	<b>13</b>
<b>12 Marking.....</b>	<b>14</b>
12.1 General.....	14
12.2 Minimum required marking.....	14
12.3 Additional marking.....	14
<b>Annex A (normative) Establishment of the pipe material classification.....</b>	<b>15</b>

<b>Annex B (normative) Minimum depth of engagement of sockets</b> .....	<b>18</b>
<b>Annex C (normative) Temperature derating factor</b> .....	<b>21</b>
<b>Annex D (informative) Calculation of negative pressure capability of pipes</b> .....	<b>22</b>
<b>Annex E (normative) Determination of axial and circumferential orientation factor</b> .....	<b>23</b>
<b>Bibliography</b> .....	<b>25</b>