

ISO 16422-2:2024-02 (E)

Pipes and joints made of oriented unplasticized poly(vinyl chloride) (PVC-O) for the conveyance of water under pressure - Part 2: Pipes

Contents

Page

Foreword.....	iv
Introduction.....	v
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	2
4 Symbols.....	4
5 Material.....	5
5.1 General.....	5
5.2 Density.....	5
5.3 MRS class.....	6
5.4 Orientation factor.....	6
6 General characteristics.....	6
6.1 Appearance.....	6
6.2 Colour.....	6
6.3 Opacity.....	6
6.4 Classification of pipes.....	7
6.4.1 Classification.....	7
6.4.2 Calculation of wall thickness.....	7
7 Geometrical characteristics.....	7
7.1 Measurement of dimensions.....	7
7.2 Length of pipes.....	7
7.3 Nominal outside diameters and wall thicknesses.....	7
7.4 Pipes with integral sockets with elastomeric sealing ring type.....	9
7.5 Plain ends.....	11
8 Selection of pipes.....	11
8.1 Selection of nominal pressure and pipe series S for water up to and including 25 °C.....	11
8.2 Determination of the allowable operating pressure for water up to 45 °C.....	11
9 Mechanical characteristics.....	11
9.1 Resistance to hydrostatic pressure.....	11
9.1.1 General.....	11
9.1.2 Pipes.....	12
9.1.3 Pipes with integral sockets.....	12
9.2 Impact strength.....	12
9.3 Ring stiffness.....	13
10 Physical characteristics.....	13
11 Sealing rings.....	13
12 Marking.....	14
12.1 General.....	14
12.2 Minimum required marking.....	14
12.3 Additional marking.....	14
Annex A (normative) Establishment of the pipe material classification.....	15

Annex B (normative) Minimum depth of engagement of sockets	18
Annex C (normative) Temperature derating factor	21
Annex D (informative) Calculation of negative pressure capability of pipes	22
Annex E (normative) Determination of axial and circumferential orientation factor	23
Bibliography	25