

ISO/TS 23927:2024-03 (E)

Laminates and moulding compounds - Prepregs - Determination of tack

| Contents | | Page |
|---|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 Scope | | 1 |
| 2 Normative references | | 1 |
| 3 Terms and definitions | | 1 |
| 4 Principle | | 1 |
| 5 Apparatus | | 2 |
| 5.1 Probe | | 3 |
| 5.2 Support platen | | 3 |
| 5.3 Force measurement system | | 3 |
| 5.4 Tension/compression testing machine | | 4 |
| 5.4.1 General | | 4 |
| 5.4.2 Test speed | | 4 |
| 5.4.3 Recording of data | | 4 |
| 6 Test specimens | | 4 |
| 7 Number of test specimens | | 4 |
| 8 Conditioning | | 4 |
| 9 Procedure | | 4 |
| 9.1 Test atmosphere | | 4 |
| 9.2 Probe setting | | 4 |
| 9.3 Specimen seating | | 4 |
| 9.4 Test | | 5 |
| 9.4.1 General | | 5 |
| 9.4.2 Contacting the specimen | | 5 |
| 9.4.3 Measurement of the tack force | | 5 |
| 10 Expression of result | | 6 |
| 10.1 Tack | | 6 |
| 10.2 Tack strength | | 6 |
| 11 Test report | | 6 |
| Annex A (informative) Determination of tack — Example | | 7 |
| Annex B (informative) Example of a probe and a self-aligning jig | | 8 |
| Bibliography | | 10 |