

ISO/PAS 22101-3:2024-07 (E)

Polyethylene reinforced with short glass fibres (PE-sGF) piping systems for industrial applications - Part 3: Fittings

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	2
3	Terms and definitions	2
4	Material	3
4.1	PE compound	3
4.2	PE-sGF compound	3
4.3	Material for non-polyethylene-based parts	3
4.3.1	General	3
4.3.2	Metal parts	3
5	General characteristics	3
5.1	Appearance	3
5.2	Design	3
5.3	Colour	4
5.4	Electrical characteristics for electrofusion fittings	4
5.5	Appearance of factory-made joints	4
6	Geometrical characteristics	4
6.1	Measurement of dimensions	4
6.2	Dimensions of electrofusion socket	5
6.2.1	Diameters and lengths of electrofusion socket fitting	5
6.2.2	Wall thickness of the fitting body	5
6.3	Dimensions of fabricated fittings	6
6.4	Dimensions of loose backing flanges and flange adapters	6
7	Mechanical characteristics	8
7.1	General	8
7.2	Conditioning	8
7.3	Requirements	8
8	Physical characteristics	10
8.1	Conditioning	10
8.2	Requirements	10
9	Chemical resistance of fittings in contact with chemicals	11
10	Performance requirements	11
11	Marking	11
11.1	General	11
11.2	Minimum required marking	11
11.3	Fusion system recognition	12
12	Packaging	12
Annex A (normative)	Fabricated fittings	13
Annex B (normative)	Short-term pressure test method	19
Annex C (normative)	Specific characteristics for butt fused joints of polyethylene reinforced with short glass fibre (PE-sGF) piping systems for industrial applications	21
Bibliography		25