

# ISO 7617-1:2024-08 (E)

## Plastics-coated fabrics for upholstery - Part 1: Specification for PVC-coated knitted fabrics

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>4</b>	<b>Sampling .....</b>	<b>2</b>
<b>5</b>	<b>Testing and compliance .....</b>	<b>2</b>
<b>6</b>	<b>Requirements .....</b>	<b>3</b>
<b>6.1</b>	<b>Preliminary inspection .....</b>	<b>3</b>
<b>6.1.1</b>	<b>General .....</b>	<b>3</b>
<b>6.1.2</b>	<b>Visual inspection .....</b>	<b>3</b>
<b>6.1.3</b>	<b>Fusion .....</b>	<b>3</b>
<b>6.2</b>	<b>Colour, embossing and finish .....</b>	<b>3</b>
<b>6.3</b>	<b>Dimensions .....</b>	<b>4</b>
<b>6.3.1</b>	<b>Usable width .....</b>	<b>4</b>
<b>6.3.2</b>	<b>Length of coated fabric in a roll .....</b>	<b>4</b>
<b>6.3.3</b>	<b>Thickness .....</b>	<b>4</b>
<b>6.4</b>	<b>Physical requirements .....</b>	<b>4</b>
<b>6.4.1</b>	<b>Mass of coating per unit area .....</b>	<b>4</b>
<b>6.4.2</b>	<b>Mechanical properties .....</b>	<b>4</b>
<b>6.4.3</b>	<b>Surface properties .....</b>	<b>4</b>
<b>6.4.4</b>	<b>Properties after ageing .....</b>	<b>4</b>
<b>6.4.5</b>	<b>Fire behaviour .....</b>	<b>5</b>
<b>7</b>	<b>Marking .....</b>	<b>6</b>
<b>8</b>	<b>Test report .....</b>	<b>7</b>
<b>Annex A (normative) Method of selecting test specimens .....</b>		<b>8</b>
<b>Annex B (normative) Determination of resistance to print wear .....</b>		<b>11</b>