

# DIN EN 1254-3:2025-04 (E)

## Copper and copper alloys - Plumbing fittings - Part 3: Compression fittings for use with plastics and multilayer pipes (includes Amendment A1:2025)

---

| <b>Contents</b>  |  | <b>Page</b> |
|--|--|-------------|
| European foreword.....   |  | 4           |
| Introduction .....   |  | 6           |
| 1 Scope.....   |  | 7           |
| 2 Normative references.....  |  | 8           |
| 3 Terms and definitions .....  |  | 10          |
| 4 Product characteristics.....   |  | 10          |
| 4.1 Internal pressure .....  |  | 10          |
| 4.2 Tightness.....   |  | 10          |
| 4.3 Resistance to high temperature for fittings with elastomeric seals (for heating networks)..... |  | 11          |
| 4.4 Release of dangerous substances.....   |  | 11          |
| 4.5 Durability.....  |  | 12          |
| 4.6 Wall thickness at the threaded portions of fittings and/or compression nut .....               |  | 12          |
| 4.7 Dimensions of tail pipe ends for swivel fittings.....  |  | 12          |
| 4.8 Dimensions of gas union connectors .....   |  | 13          |
| 4.9 Threaded end dimensions .....  |  | 13          |
| 4.10 Other adapter ends (not defined in $\text{A1}$ EN 1254-20:2021+A1:2025 $\text{A1}$ ).....     |  | 13          |
| 4.11 Bore dimensions.....  |  | 13          |
| 4.12 Identity of elastomeric sealing material for liquid applications .....                        |  | 13          |
| 4.13 Identity of elastomeric sealing material for gas applications.....                            |  | 13          |
| 4.14 Pipe abutment .....   |  | 14          |
| 4.15 Alignment of the fitting ends.....  |  | 14          |
| 4.16 Shapes for tightening systems.....  |  | 14          |
| 4.17 Surface condition .....   |  | 14          |
| 4.18 Plated or coated surfaces .....   |  | 14          |
| 4.19 $\text{A1}$ Wall thickness of the fitting body $\text{A1}$ .....                              |  | 14          |
| 5 Testing, assessment and sampling methods .....   |  | 14          |
| 5.1 General.....   |  | 14          |
| 5.2 Internal pressure .....  |  | 15          |
| 5.3 Tightness.....   |  | 16          |
| 5.4 Durability.....  |  | 20          |
| 5.5 Wall thickness at threaded portions of adaptor fittings.....                                   |  | 20          |
| 5.6 Dimensions of tail pipe ends for swivel fittings.....  |  | 21          |
| 5.7 Dimensions of gas union connectors .....   |  | 21          |
| 5.8 Threaded end dimensions .....  |  | 21          |
| 5.9 Bore dimensions.....   |  | 21          |
| 5.10 Identity of elastomeric sealing material for liquid applications .....                        |  | 21          |
| 5.11 Identity of elastomeric sealing material for gas applications.....                            |  | 21          |
| 5.12 Alignment of the fitting ends.....  |  | 21          |
| 5.13 $\text{A1}$ Wall thickness of the fitting body $\text{A1}$ .....                              |  | 22          |
| 6 Evaluation of conformity .....   |  | 22          |
| 6.1 General.....   |  | 22          |
| 6.2 Type testing.....  |  | 22          |
| 6.3 Factory production control (FPC) .....   |  | 28          |

|            |  |           |
|------------|--|-----------|
| <b>7</b>   | <b>Designation.....</b>  | <b>31</b> |
| <b>8</b>   | <b>Marking, labelling and packaging .....</b>                                | <b>31</b> |
| <b>8.1</b> | <b>General.....</b>  | <b>31</b> |
| <b>8.2</b> | <b>Additional marking.....</b>   | <b>31</b> |
| <b>8.3</b> | <b>Dezincification resistant copper zinc alloys .....</b>                    | <b>32</b> |
|            | <b>Annex A (normative) Operating temperatures and design pressures .....</b> | <b>33</b> |
|            | <b>Bibliography .....</b>  | <b>35</b> |