

ISO 11357-6:2025-06 (E)

Plastics - Differential scanning calorimetry (DSC) - Part 6: Determination of oxidation induction time (isothermal OIT) and oxidation induction temperature (dynamic OIT)

| Contents | | Page |
|--------------------|---|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Principle | 2 |
| 4.1 | General | 2 |
| 4.2 | Oxidation induction time (isothermal OIT) | 2 |
| 4.3 | Oxidation induction temperature (dynamic OIT) | 2 |
| 5 | Apparatus and materials | 2 |
| 5.1 | General | 2 |
| 5.2 | DSC instrument | 3 |
| 5.3 | Crucibles | 3 |
| 5.4 | Flowmeter | 3 |
| 5.5 | Oxygen | 3 |
| 5.6 | Air | 3 |
| 5.7 | Nitrogen | 3 |
| 5.8 | Gas-selector switch and regulators | 3 |
| 6 | Test specimens | 4 |
| 6.1 | General | 4 |
| 6.2 | Specimens from compression-moulded plates | 4 |
| 6.3 | Specimens from injection-moulded plates or melt flow extrudates | 4 |
| 6.4 | Specimens from finished parts | 4 |
| 7 | Test conditions and specimen conditioning | 5 |
| 8 | Calibration | 5 |
| 8.1 | Oxidation induction time (isothermal OIT) | 5 |
| 8.1.1 | General | 5 |
| 8.1.2 | Dynamic temperature calibration | 5 |
| 8.1.3 | Isothermal stepwise temperature calibration | 5 |
| 8.2 | Oxidation induction temperature (dynamic OIT) | 5 |
| 9 | Procedure | 6 |
| 9.1 | Setting up the instrument | 6 |
| 9.2 | Loading the test specimen into the crucible | 6 |
| 9.3 | Insertion of crucibles | 6 |
| 9.4 | Nitrogen, air and oxygen flow | 6 |
| 9.5 | Sensitivity adjustment | 6 |
| 9.6 | Performance of measurement | 6 |
| 9.6.1 | Oxidation induction time (isothermal OIT) | 6 |
| 9.6.2 | Oxidation induction temperature (dynamic OIT) | 7 |
| 9.7 | Cleaning | 8 |
| 10 | Expression of results | 8 |
| 11 | Precision and bias | 10 |
| 12 | Test report | 10 |
| Bibliography | | 12 |