DIN EN 1555-4:2026-02 (E)

Plastics piping systems for the supply of gaseous fuels - Polyethylene (PE) - Part 4: Valves

Contents

Page

European foreword 4

Introduction 5

1 Scope 6

2 Normative references 6

3 Terms and definitions 8
3.1 General 8
3.2 Terms relating to design 8

4 Symbols and abbreviations 9

5 Material 9
5.1 PE compound for valves 9
5.2 Material for non-polyethylene components 9
5.2.1 General 9
5.2.2 Metal parts 10
5.2.3 Sealing materials 10
5.2.4 Greases and lubricants 10
5.2.5 Assembly 10

6 General characteristics 10
6.1 Appearance of the valve 10
6.2 Colour 10
6.3 Design 10
6.3.1 General 10
6.3.2 Valve body 10
6.3.3 Valve ends 10
6.3.4 Operating device 11
6.3.5 Seals 11

7 Geometrical characteristics 11
7.1 General 11
7.2 Measurement of dimensions 11
7.3 Dimensions of spigot ends for valves 11
7.4 Dimensions of valves with electrofusion sockets 11
7.5 Dimensions of the operating device 11

8 Mechanical characteristics of assembled valves 11
8.1 General 11
8.2 Requirements 12
8.2.1 General 12
8.2.2 Air flow rate 18

9 Physical characteristics 19
9.1 Conditioning 19
9.2 Requirements 19

10 Performance requirements 19

11 Technical file 19

12 Marking 20
12.1 General 20
12.2 Minimum required marking 20
12.3 Additional marking 21

13 Delivery conditions 21

Annex A (normative) Determination of the leaktightness of seat(s) and packing 22

A.1 General 22
A.2 Test piece 22
A.3 Procedure 22
A.3.1 Conditioning 22
A.3.2 Internal leaktightness test (fully closed valve) 22
A.3.3 External leaktightness test (half open valve) 22
A.4 Test report 23

Annex B (normative) Test method for leaktightness and ease of operation after tensile loading 24

B.1 Apparatus 24
B.2 Test piece 24
B.3 Conditions 24
B.4 Procedure 24
B.5 Test report 25

Bibliography 26