

DIN EN 10284:2026-05 (E)

Malleable cast iron fittings with compression ends for polyethylene (PE) piping systems

Contents		Page
European foreword		4
1	Scope	6
2	Normative references	6
3	Terms and definitions	7
4	Types of fittings	10
5	Materials	10
5.1	General	10
5.2	Material of the fitting body	10
5.3	Material of the fitting components	10
5.4	Elastomers	10
6	Corrosion protection	11
6.1	General	11
6.2	Hot dip galvanizing	11
6.2.1	General	11
6.2.2	Chemical composition of the hot dip zinc coating	11
6.2.3	Coating mass per surface unit and layer thickness	11
6.2.4	Surface conditions of the hot dip zinc coating	12
6.3	Non-metallic coating	12
6.4	Dangerous substances	12
6.4.1	General	12
6.4.2	Hot dip zinc coating	12
6.4.3	Dispatch conditions of finished fittings	12
6.4.4	Non-metallic coating	12
7	Design	12
7.1	General	12
7.2	Geometrical characteristics	12
7.3	Minimum bore	13
7.4	Supporting sleeve	13
7.5	Pipe threads	14
7.6	Surfaces	14
7.7	Transition fittings	14
7.7.1	Transition with jointing thread	14
7.7.2	Transition for steel pipe	14
7.7.3	Transition for other pipes	14
7.8	Load transmission	14
8	Performance requirements	15
8.1	Yield strength	15
8.2	Tightness	15
8.2.1	Internal pressure strength	15
8.2.2	Leak tightness	15
8.3	Pressure and temperature limits	15
8.4	Dimensional tolerances	16
8.5	Reaction to fire	16

8.6	Durability	16
8.6.1	Durability of fittings	16
8.6.2	Durability of elastomeric seals	16
8.7	Dangerous substances	16
9	Test requirements	16
9.1	General	16
9.2	Component test	19
9.2.1	Testing of malleable cast iron	19
9.2.2	Testing of plastic components	19
9.2.3	Testing of sealing materials	19
9.2.4	Testing of hot dip zinc coating	19
9.2.5	Analysis of polycyclic aromatic hydrocarbons	19
9.2.6	Testing of non-metallic coating	19
9.2.7	Visual inspection	19
9.2.8	Geometrical characteristics	19
9.2.9	Leak tightness of fitting body	20
9.3	Assembly test	20
9.3.1	General	20
9.3.2	Leak tightness under internal pressure	20
9.3.3	Long-term leak tightness under internal pressure	21
9.3.4	Resistance to tensile loading at 23°C	21
9.3.5	Resistance to pull out at 23 °C	22
9.3.6	Resistance to end load at 80 °C	22
9.3.7	Leak tightness after temperature cycling (outside temperature)	23
9.3.8	Leak tightness under internal pressure when subjected to bending	24
9.3.9	Behaviour in case of negative pressure (Vacuum)	25
9.3.10	Surface protection - testing by salt spray test	25
10	Manufacture	25
11	Designation of fittings	25
11.1	Elements of the designation for ordering	25
11.2	Additional notes on designation of size	26
11.3	Examples of designation	26
12	Marking	26
Annex A (normative) Surface protection - Salt spray test		27
A.1	Requirements	27
A.2	Testing	27
Bibliography		28