ISO 19935-2:2026-05 (E)

Plastics - Temperature modulated DSC - Part 2: Measurement of specific heat capacity c_p

Contents

Page

Foreword ... iv

Introduction ... v

1 Scope ... 1

2 Normative references ... 1

3 Terms and definitions ... 1

4 Symbols and abbreviated terms ... 1
4.1 Temperature modulation, *T(t)* ... 1
4.2 Scanning rate ... 1
4.3 Heat flow rate, Φ(t) ... 1

5 Principles of determination of specific heat capacity with temperature modulated DSC ... 2
5.1 General ... 2
5.2 Specific heat capacity with no processes ... 2
5.3 Reversing and non-reversing specific heat capacity ... 2
5.4 Step scan method ... 2
5.5 Multiple frequencies ... 2

6 Apparatus and materials ... 2
6.1 General ... 2
6.2 Temperature control of the modulated differential scanning calorimeter ... 2

7 Calibration ... 3
7.1 General ... 3
7.2 Calibration of modulation amplitude ... 3
7.3 Calibration of phase ... 3

8 Procedure ... 3
8.1 General ... 3
8.2 Calculation of the specific heat capacity ... 3
8.3 Examples of the results ... 4
8.3.1 Modulated heat flow rate and scanning rate of modulation ... 4
8.3.2 Determination of specific heat capacity ... 4

9 Precision and bias ... 5

10 Test report ... 5

Annex A (informative) **Example of the c_p values of polystyrene (PS)** ... 7

Annex B (informative) **Example of the calibration constant** K(ω) **determined with the literature values of** α-Al_2O_3 [4] ... 8

Annex C (informative) **Example of a reversing heat flow rate curve based on a modulated heat flow rate curve and a comparison with the specific heat capacity** ... 9

Annex D (informative) **Example of determination of specific heat capacity based on a multifrequency modulated heat flow rate curve** ... 10

Bibliography ... 13