

ISO 19935-2:2026-05 (E)

Plastics - Temperature modulated DSC - Part 2: Measurement of specific heat capacity c_p

Contents

Page

Foreword.....	iv
Introduction.....	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviated terms	1
4.1 Temperature modulation, $T(t)$	1
4.2 Scanning rate.....	1
4.3 Heat flow rate, $\Phi(t)$	1
5 Principles of determination of specific heat capacity with temperature modulated DSC	2
5.1 General.....	2
5.2 Specific heat capacity with no processes.....	2
5.3 Reversing and non-reversing specific heat capacity.....	2
5.4 Step scan method.....	2
5.5 Multiple frequencies.....	2
6 Apparatus and materials	2
6.1 General.....	2
6.2 Temperature control of the modulated differential scanning calorimeter.....	2
7 Calibration	3
7.1 General.....	3
7.2 Calibration of modulation amplitude.....	3
7.3 Calibration of phase.....	3
8 Procedure	3
8.1 General.....	3
8.2 Calculation of the specific heat capacity.....	3
8.3 Examples of the results.....	4
8.3.1 Modulated heat flow rate and scanning rate of modulation.....	4
8.3.2 Determination of specific heat capacity.....	4
9 Precision and bias	5
10 Test report	5
Annex A (informative) Example of the c_p values of polystyrene (PS)	7
Annex B (informative) Example of the calibration constant $K(\omega)$ determined with the literature values of $\alpha\text{-Al}_2\text{O}_3$ ^[4]	8
Annex C (informative) Example of a reversing heat flow rate curve based on a modulated heat flow rate curve and a comparison with the specific heat capacity	9
Annex D (informative) Example of determination of specific heat capacity based on a multifrequency modulated heat flow rate curve	10
Bibliography	13