DIN EN 12608-1:2026-10 (E)

Unplasticized poly(vinyl chloride) (PVC-U) profiles for the fabrication of windows and doors - Classification, requirements and test methods - Part 1: Non-covered PVC-U profiles

Contents

Page

European foreword 4

1 Scope 6

2 Normative references 6

3 Terms and definitions 7

4 Classifications 10
4.1 General 10
4.2 Classification of climatic zones 10
4.3 Classification of material to the resistance to artificial weathering 11
4.4 Classification of main profiles according to the wall thickness of the external walls 11

5 Requirements 12
5.1 Material 12
5.2 Appearance 13
5.3 Dimensions and tolerances 13
5.3.1 General 13
5.3.2 Nominal shape 13
5.3.3 Wall thickness of main profiles 14
5.3.4 Tolerances on other dimensions 14
5.3.5 Deviation from straightness of the main profiles 14
5.4 Linear weight of the main profiles 14
5.5 Heat reversion 14
5.5.1 Main profiles 14
5.5.2 Auxiliary profiles 14
5.6 Behaviour after heating at 150 °C 14
5.7 Weldability 14
5.7.1 General 14
5.7.2 Tensile bending test 14
5.7.3 Compression bending test 15
5.8 Optional properties 15

6 Test methods 15
6.1 Visual inspection 15
6.2 Determination of dimensions 15
6.2.1 Measuring devices 15
6.2.2 Test specimen 15
6.2.3 Conditioning 15
6.2.4 Procedure 15
6.3 Determination of the linear weight of the profile 16
6.3.1 General 16
6.3.2 Using a balance 16
6.4 Determination of the thickness of a co-extruded layer 17
6.5 Determination of colorimetric coordinates 17
6.6 Determination of the ash content 17
6.7 Determination of the resistance of main profiles to impact by falling mass 17

7 Traceability 18

Annex A (normative) Requirements for materials 19

A.1 General 19
A.2 Preparation of test specimens 22
A.2.1 General 22
A.2.2 Preparation of pressed plates 22
A.2.3 Material properties 22

Annex B (normative) Calculation method for the determination of the radiant exposure and exposure time to be used for artificial weathering 23

B.1 General 23
B.2 Calculation 23

Bibliography 26