DIN EN 12608-3:2026-12 (E)

Unplasticized poly(vinyl chloride) (PVC-U) profiles for the fabrication of windows and doors - Classification, requirements and test methods - Part 3: PVC-U profiles covered with paint

Contents

Page

European foreword 3

1 Scope 4

2 Normative references 4

3 Terms and definitions 5

4 Classifications 5
4.1 General 5
4.2 Classification of main base profiles according to the wall thickness of the external walls 5
4.3 Classification of materials used for base profiles according to the resistance to artificial weathering 5
4.4 Classification of paints according to the resistance to artificial weathering 6

5 Requirements for base profiles 6
5.1 Base profiles according to EN 12608-1 6
5.2 Other base profiles 6
5.2.1 Material 6
5.2.2 Appearance 6
5.2.3 Dimensions and tolerances 7
5.2.4 Linear weight 7
5.2.5 Heat reversion 7
5.2.6 Resistance to impact by falling mass 7

6 Requirements for paints 7
6.1 General 7
6.2 Resistance to artificial weathering 7
6.3 Solar direct reflectance 7

7 Requirements for painted profiles 8
7.1 General 8
7.2 Appearance 8
7.3 Colour 8
7.4 Deviation from straightness of the painted main profiles 9
7.5 Resistance to cross-cut 9
7.6 Layer thickness 9
7.7 Strength of welded corners and T-joints of painted main profiles 9

8 Test methods 9
8.1 Visual inspection 9
8.2 Determination of colorimetric coordinates 9
8.3 Artificial weathering 9

9 Traceability 10

Annex A (normative) Determination of the reflection behaviour of paints by spectral analysis 11