

# ISO 8483:2003-12 (E)

## Glass-reinforced thermosetting plastics (GRP) pipes and fittings - Test methods to prove the design of bolted flange joints

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Principle .....</b>	<b>1</b>
<b>3</b>	<b>Apparatus .....</b>	<b>2</b>
3.1	End-sealing devices .....	2
3.2	Supports .....	2
3.3	Source of hydrostatic pressure .....	2
3.4	Means of measuring the gauge pressure .....	2
3.5	Vacuum pump or equivalent .....	2
3.6	Bolt torque test apparatus .....	2
<b>4</b>	<b>Test pieces .....</b>	<b>3</b>
4.1	Test arrangement .....	3
4.2	Number of test pieces .....	4
<b>5</b>	<b>Conditioning .....</b>	<b>4</b>
<b>6</b>	<b>Test temperature .....</b>	<b>4</b>
<b>7</b>	<b>Procedures .....</b>	<b>4</b>
7.1	General .....	4
7.2	Leaktightness when subjected to an external pressure differential .....	5
7.3	Initial leakage .....	5
7.4	Resistance to internal pressure .....	7
7.5	Resistance of the joint to bending and pressure including hydrostatic end thrust .....	7
7.6	Short-duration resistance to internal pressure including hydrostatic end thrust .....	8
7.7	Resistance to bolt-tightening torque .....	9
7.8	Testing excluding hydrostatic end thrust (see 7.1) .....	9
<b>8</b>	<b>Test report .....</b>	<b>9</b>
<b>Annex A (normative)</b>	<b>Equations for calculating the additional force, <math>F</math>, and limiting deflection, <math>\delta</math>, for the bending test described in 7.5 .....</b>	<b>11</b>