

DIN EN ISO 12086-2:2006-05 (E)

Plastics - Fluoropolymer dispersions and moulding and extrusion materials - Part 2: Preparation of test specimens and determination of properties (ISO 12086-2:2006)

Contents		Page
Foreword		2
1	Scope	4
2	Normative references	4
3	Terms and definitions	6
4	Abbreviated terms and symbols	7
5	Sampling	8
6	Preparation of test specimens	8
7	Conditioning and test conditions	8
8	General testing of fluoropolymers	8
8.1	Electrical properties	9
8.2	Mechanical properties	11
8.3	Thermal-transition temperatures	13
8.4	Density	14
8.5	Flammability by oxygen index	14
8.6	Particle size and size distribution	14
9	Testing of fluoropolymer dispersions	20
9.1	General	20
9.2	Preparation of test samples	21
9.3	Isolation of PTFE from dispersion	21
9.4	Coagulum in dispersions	22
9.5	Percentage polymer and surfactant in aqueous dispersion	22
9.6	PTFE solids content by hydrometer	23
9.7	pH of dispersions	24
10	Testing of PTFE and closely related materials	24
10.1	General	24
10.2	Preparation of test specimens by moulding	24
10.3	Bulk density	26
10.4	Extrusion pressure	30
10.5	Powder-flow time	35
10.6	Standard specific gravity (SSG), extended specific gravity (ESG) and thermal-instability index (TII)	37
10.7	Stretching-void index (SVI)	40
11	Testing of conventionally melt-processible fluoropolymers	41
11.1	Preparation of test specimens by moulding	41
11.2	Melt mass-flow rate (MFR) and melt volume-flow rate (MVR)	42
12	Other test methods used with fluoropolymers	44
12.1	Brittleness temperature of plastics and elastomers by impact	44
12.2	Coefficients of static and kinetic friction	44
12.3	Zero-strength time	44

Annex A (informative) Listing of test methods (alphabetical order)	45
Annex B (informative) Designatory properties for common fluoropolymer types with cross-reference listing to the tables for codes in ISO 12086-1 and the test methods in ISO 12086-2	46
Bibliography	48