ISO 17484-1:2006-10 (E)

Plastics piping systems - Multilayer pipe systems for indoor gas installations with a maximum operating pressure up to and including 5 bar (500 kPa) - Part 1: Specifications for systems

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 2

3 Terms, definitions and symbols 3
3.1 Structural definitions 3
3.2 Geometrical definitions 3
3.3 Definitions related to pressure 4
3.4 Materials definitions 4
3.5 Definitions related to material characteristics 5
3.6 Terms related to service conditions 5

4 Requirements for the system 6
4.1 Pressure drop 6
4.2 Bending 6
4.3 Corrosive conditions 6

5 Pipes 6
5.1 Material 6
5.2 General characteristics 7
5.3 Dimensions of pipes 7
5.4 Mechanical properties 8
5.5 Physical properties 9

6 Fittings 10
6.1 General 10
6.2 Materials 11
6.3 Dimensions 11
6.4 Transition fittings 11
6.5 Rubber rings 11

7 Fitness for purpose 11
7.1 Diameter classes 11
7.2 Relation between maximum operating pressure and qualification test pressure 11
7.3 Requirements 12

8 Marking and documentation 13
8.1 Legibility 13
8.2 Damage 13
8.3 Minimum marking requirements 13

Annex A (normative) List of the reference product standards 15

Annex B (normative) Test for delamination and strength of the joint line 16

Annex C (normative) Resistance to gas constituents **18**

Annex D (normative) Thermal durability of the outer layer of M-pipes **19**

Annex E (normative) Adhesion test **21**

Annex F (normative) Odour permeability **22**

Annex G (normative) Resistance to tensile load on joints **23**

Annex H (normative) Crush test on joints **25**

Annex I (normative) Impact resistance test on joints **27**

Annex J (normative) Thermal cycling test on joints **29**

Annex K (normative) Repeated bending test **31**

Bibliography **33**