ISO 21367:2007-05 (E)

Plastics - Reaction to fire - Test method for flame spread and combustion product release from vertically oriented specimens

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Symbols 3

5 General principles 3

6 Test apparatus 4

7 Test specimen 13
7.1 Surface characteristics 13
7.2 Exposed surface 13
7.3 Number and size of specimen 13
7.4 Construction of specimen 14
7.5 Conditioning of specimens 14
7.6 Preparation 14

8 Test environment 16

9 Calibration 16
9.1 Preliminary calibration 16
9.2 Operating calibrations 17
9.3 Less frequent calibrations 18

10 Test procedure 19
10.1 Warning 19
10.2 Initial preparation 19
10.3 Procedure 20

11 Calculation 21
11.1 Calibration constant for oxygen consumption analysis 21
11.2 Heat release rate 21
11.3 Exhaust duct flow rate 22
11.4 Smoke production rate (SPR) 22

12 Test report 23

Annex A (normative) Additional calculations 24

Annex B (informative) Simplified version of the apparatus 26

Annex C (informative) Repeatability of the test method 28

Annex D (informative) Calibration of the working heat flux meter 32

Bibliography 33