

DIN EN 16902:2017-04 (E)

Commercial beverage coolers - Classification, requirements and test conditions

Contents		Page
European foreword		6
1	Scope	7
2	Normative references	7
3	Terms and definitions	7
3.1	Types of commercial beverage cooler	7
3.2	Parts of commercial beverage cooler	8
3.3	Physical aspects and dimensions	9
3.4	Definitions relating to performance characteristics	10
3.5	Definition related to test environment	12
4	Symbols	13
5	Classification and requirements	13
5.1	Classification according to temperature	13
Table 1 -- Classification according to temperature		14
5.2	Construction	14
5.2.1	General	14
5.2.2	Materials	14
5.2.3	Thermal insulation	15
5.2.4	Refrigerating system	15
5.2.5	Electrical components	16
6	Tests	16
6.1	General	16
Table 2 -- Test summary		16
6.2	Tests outside test room	17
6.2.1	General	17
6.2.2	Seal test for doors and lids	17
6.2.3	Test on durability of door and lid	17
Figure 1 -- Durability of lids and doors		18
6.2.4	Linear dimensions, areas and volumes	18
6.3	Tests inside test room	18
6.3.1	General	18
6.3.2	Test room condition	19
Table 3 -- Test room climate classes and half reload test		20
Figure 2 -- Climate measuring point for horizontal commercial beverage cooler		20
Figure 3 -- Climate measuring point for semi vertical commercial beverage cooler		21
Figure 4 -- Climate measuring point for vertical open commercial beverage cooler		22
Figure 5 -- Climate measuring point for vertical closed commercial beverage cooler		22
6.3.3	M-can	23
6.3.4	Preparation of test commercial beverage cooler and general test procedures	23

Figure 6 -- Cabinet location within test room	24
Figure 7 -- Air movement	25
6.3.5 Loading the commercial beverage cooler	26
Figure 8 -- Commercial beverage cooler sectional view	26
Figure 9 -- Commercial beverage cooler front view: loading phase 1	27
Figure 10 -- Commercial beverage cooler front view: loading phase 2	27
Figure 11 -- Commercial beverage cooler front view glass door merchandiser shelf	28
Figure 12 -- Commercial beverage cooler: single-door merchandiser bottom shelf top view	28
Figure 13 -- Commercial beverage cooler: double-door merchandiser bottom shelf top view	28
Figure 14 -- Commercial beverage cooler: double-door merchandiser second and fourth shelves top view	29
Figure 15 -- Commercial beverage cooler: triple-door merchandiser bottom shelf top view	29
Figure 16 -- Commercial beverage cooler: triple-door merchandiser second and fourth shelves top view	30
Figure 17 -- Horizontal commercial beverage cooler: single-door front view	30
Figure 18 -- Horizontal commercial beverage cooler top view	31
Figure 19 -- Horizontal commercial beverage cooler double door top view	31
Figure 20 -- Horizontal commercial beverage cooler triple door top view	31
Figure 21 -- Horizontal commercial beverage cooler double door, with less than 8 cans across, top view	32
Figure 22 -- Round barrel commercial beverage cooler top view	32
Figure 23 -- Round barrel commercial beverage cooler front view	33
6.3.6 Running in period	33
6.3.7 Stable conditions	33
6.3.8 Lighting and night-covers	34
Figure 24 -- Beverage coolers with lighting and night-cover test procedure	34
6.3.9 Power supply	34
6.3.10 Testing several commercial beverage coolers in the same room	34
6.3.11 Temperature test	35
Figure 25 -- Relevant temperature curves of M-cans	36
Figure 26 -- Arithmetic mean temperature of M-cans (curve d)	36
Table 4 -- Door or night cover opening time related to the cooler total capacity	38
Figure 27 -- Commercial beverage cooler fitted with energy management device (EMD) test procedure	40
Figure 28 -- EMD test	41
6.3.12 Water vapour condensation test	41

Figure 29 -- Condensation code	42
6.3.13 Electrical energy consumption test	42
6.3.14 Calculation of specific energy consumption (SEC)	43
6.4 Test report	43
Table 5 -- Details of the cabinet under test, test conditions and preparation for test	43
Table 6 -- Results of electrical energy consumption test	45
Table 7 -- Results of other tests	45
7 Marking	45
7.1 Load limit	45
Figure 30 -- Load limit markings	46
Figure 31 -- Dimensions of load limit line	46
Figure 32 -- Different positions for the load limit	46
7.2 Marking plate	47
7.3 Information to be supplied by the manufacturer	47
Annex A (informative) Commercial beverage cooler family	48
Table A.1 -- Commercial beverage cooler family	48
Annex B (normative) Net volume calculation	49
B.1 General	49
B.2 Calculation of net volume	49
Figure B.1 -- Net volume calculation	49
Annex C (normative) Equivalent volume calculation	50
C.1 General	50
C.2 Calculation of equivalent volume	50
C.3 Gross volume measurements	50
Annex D (normative) TDA calculation	52
D.1 General	52
D.2 Measurement of TDA in a refrigerated display cabinet - Calculation of TDA	52
Figure D.1 -- Vertical, multi-deck and semi-vertical cabinets	53
Figure D.2 -- Combined, glass door top, open bottom, cabinet	54
Figure D.3 -- Horizontal, open, island cabinets	55
Figure D.4 -- Vertical, glass door, cabinet	56
Annex E (informative) Test for absence of odour and taste	57
E.1 Preparation and testing	57
E.1.1 Ambient temperature	57
E.1.2 Cleaning	57
E.1.3 Thermostat setting	57
E.1.4 Samples	57
E.1.5 Test period	57
E.2 Examination of samples	58

E.2.1	Conditions	58
E.2.2	Evaluation	58
Annex F (normative) Performance and energy rating of commercial beverage cooler		59
F.1	Scope	59
F.2	Standard rating conditions for commercial beverage cooler	59
F.3	Specific energy consumption (SEC) for commercial beverage coolers	59
Annex ZA (informative) Relationship between this European Standard and the ecodesign requirements of Commission DRAFT Ecodesign Regulation DG ENER LOT12 aimed to be covered		60
Table ZA.1 -- Correspondence between this European Standard and Commission Draft Ecodesign Regulation DG ENER LOT12 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for refrigerated commercial display cabinets and Commission's standardization request 'M/495'		60
Bibliography		61