

DIN EN 12830:2018-10 (E)

Temperature recorders for the transport, storage and distribution of temperature sensitive goods - Tests, performance, suitability

| Contents | | Page |
|-------------------------|--|-------------|
| European foreword | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 7 |
| 4 | Concepts | 11 |
| 4.1 | General | 11 |
| 4.2 | Temperature recorder elements | 12 |
| 4.3 | Temperature recorder architecture (or configuration) | 12 |
| 4.3.1 | General | 12 |
| 4.3.2 | Monolithic instrument | 13 |
| 4.3.3 | Monolithic instrument with external relevant data | 13 |
| 4.3.4 | Temperature recorder with digital probes | 14 |
| 4.3.5 | Temperature recorder on the cloud | 15 |
| 5 | Requirements | 16 |
| 5.1 | General | 16 |
| 5.2 | Measuring range | 17 |
| 5.3 | Protection of the data from manipulation | 17 |
| 5.3.1 | General | 17 |
| 5.3.2 | Audit trail | 17 |
| 5.3.3 | Clearly readable data copies | 17 |
| 5.3.4 | Safekeeping of accessibility of the data | 17 |
| 5.3.5 | Safekeeping of readability of the data | 18 |
| 5.3.6 | Safekeeping of correctness of the data | 18 |
| 5.3.7 | Access restrictions | 18 |
| 5.3.8 | Detailed documentation of the software | 18 |
| 5.4 | Locking of settings | 18 |
| 5.5 | Recording | 18 |
| 5.5.1 | General | 18 |
| 5.5.2 | Traceability | 18 |
| 5.5.3 | Chart only for mechanical recorder | 19 |
| 5.6 | Autonomous power supply | 19 |
| 5.7 | Degree of protection provided by the enclosure | 19 |
| 5.8 | Electrical safety (if applicable) | 19 |
| 5.9 | Operating characteristics linked to external electrical influences | 20 |
| 5.9.1 | External supply voltage (if applicable) | 20 |
| 5.9.2 | Autonomous supply (if applicable) | 20 |
| 5.9.3 | Frequency (AC) (if applicable) | 20 |
| 5.9.4 | Power cut-offs | 20 |
| 5.9.5 | Electrical power disturbances and susceptibility to radiated electromagnetic field | 20 |
| 5.10 | Metrological characteristics and usage profiles | 20 |
| 5.10.1 | General | 20 |
| 5.10.2 | Metrological characteristics | 20 |
| 5.10.3 | Usage profiles | 22 |
| 5.11 | Data security | 22 |
| 5.12 | Software verification levels | 22 |

| | | |
|---|---|----|
| 6 | Test methods | 23 |
| 6.1 | Test list | 23 |
| 6.2 | General conditions for tests | 24 |
| 6.2.1 | Pre-tests adjustments | 24 |
| 6.2.2 | Normal atmospheric conditions | 24 |
| 6.2.3 | Reference conditions | 24 |
| 6.3 | Determination of temperature measurement error | 25 |
| 6.3.1 | Test method | 25 |
| 6.3.2 | Reading the recording | 25 |
| 6.3.3 | Expression of results | 25 |
| 6.4 | Determination of response time | 26 |
| 6.5 | Determination of time recording error | 26 |
| 6.6 | Action of influence quantities | 27 |
| 6.6.1 | General | 27 |
| 6.6.2 | Variation in voltage supply (if applicable) | 27 |
| 6.6.3 | Influence of ambient temperature | 27 |
| 6.6.4 | Temperature testing under storage and transport conditions for the recorder | 28 |
| 6.6.5 | Shock resistance test (if applicable) | 28 |
| 6.6.6 | Mechanical vibrations (if applicable) | 28 |
| 6.6.7 | Degrees of protection provided by enclosures (IP Code) | 29 |
| 6.6.8 | Electrical safety (if applicable) | 29 |
| 6.6.9 | Dielectric strength (if applicable) | 29 |
| 6.7 | Software test | 29 |
| 6.7.1 | Test objective | 29 |
| 6.7.2 | Test procedure | 29 |
| 7 | Conditions of acceptance | 33 |
| 7.1 | Requirements | 33 |
| 7.2 | Operating error limits | 33 |
| 8 | Marking | 34 |
| 9 | Initial and periodic verification | 34 |
| Annex A (normative) Software testing | | 35 |
| A.1 | Software test general part - Test objective | 35 |
| A.2 | Test procedure | 35 |
| A.2.1 | General | 35 |
| A.2.2 | Determine the temperature recorder subunits | 35 |
| A.2.3 | Determine the relevant software of each unit or subunit | 35 |
| A.2.4 | Define the applicable test blocks of each unit or subunit | 35 |
| A.2.5 | Determine the type of each unit or subunit | 36 |
| A.3 | Software test for type P1 and type P2 | 37 |
| A.3.1 | General | 37 |
| A.3.2 | Block G: Basic requirements | 37 |
| A.3.3 | Block L: Specific software requirements for long-term storage | 48 |
| A.3.4 | Block T: Transmission of measurement data via Communication Networks | 55 |
| A.3.5 | Block S: Software separation | 61 |
| A.3.6 | Block D: Download of relevant software | 64 |
| A.4 | Software test for type P3 | 69 |
| Annex B (informative) Manufacturer software test form | | 70 |
| B.1 | Identification | 70 |
| B.1.1 | Manufacturer identification | 70 |
| B.1.2 | Test object | 70 |
| B.1.3 | Documents list | 70 |
| B.1.4 | Define the applicable test blocks of each unit or subunit (L, T, S and D) | 71 |
| B.1.5 | Selection of the type of each unit or subunit | 71 |
| B.2 | Test requirement for type P1 and P2 | 73 |
| B.2.1 | General | 73 |

| | | |
|------------------------------|--|-----------|
| B.2.2 | Basic requirements | 73 |
| B.2.3 | Extension L: Specific software requirements for long term storage | 80 |
| B.2.4 | Extension T: Specific software requirements for data transmission | 84 |
| B.2.5 | Extension S: Specific software requirements for software separation | 87 |
| B.2.6 | Extension D: Specific software requirements | 89 |
| B.3 | Test requirement for type P3 | 93 |
| | | |
| Annex C (informative) | Example of data form describing suitability for use of equipment of a specific series (to be filled in by the manufacturer) | 94 |
| | | |
| Annex D (informative) | Expected operation time and storage capacity | 95 |
| | | |
| D.1 | Storage capacity dependent on the measurement interval | 95 |
| D.2 | Battery lifetime dependent on usage | 95 |
| | | |
| Annex E (informative) | Required access to recorded data or functions is given in Table E.1 | 96 |