

DIN EN 14624:2020-08 (E)

Performance of portable locating leak detectors and of fixed gas detectors for all refrigerants

Contents		Page
European foreword		4
Introduction		5
1	Scope	6
2	Normative references	6
3	Terms and definitions	7
4	Symbols and abbreviations	10
5	General requirements for all portable locating leak detectors and fixed gas detectors -- Refrigerant gas type(informative)	10
6	Specific requirements for portable locating leak detectors	11
6.1	Detection limits	11
6.1.1	General	11
6.1.2	Static detection limit - the leak detector probe is stationary	11
6.1.3	Dynamic detection limit - the leak detector probe is moving	11
6.1.4	Dynamic detection limit in a contaminated environment	11
6.2	Response time	11
6.3	Recovery time	11
6.4	Calibration frequency and procedure	11
7	Test apparatus for portable leak detectors	11
7.1	General	11
7.2	Calibration leaks	12
7.3	Measuring distance	12
7.4	Apparatus no. 1: detector probe stationary at the orifice of calibration leak	12
7.5	Apparatus no. 2: detector probe moved with defined speed and distance in front of a calibration leak	12
7.6	Apparatus no. 3a: Chamber with monitored concentration	14
8	Performance tests of portable leak detectors	15
8.1	General	15
8.2	Test no. 1: Static detection limits	15
8.3	Test no. 2: Dynamic detection limits	15
8.4	Test no. 3 Dynamic detection limit in a contaminated environment	16
8.5	Test no. 4: Response time	16
8.6	Test no. 5: Recovery time	16
9	Portable leak detector characteristics, reporting of test results and requirements	17
9.1	Reporting of test result	17
9.2	Minimum product requirements	17
10	Service and maintenance -- Portable locating leak detectors -- Periodic check and calibration	18
11	Technical specification and product information -- Portable locating leak detectors	18

12	Specific requirements for fixed gas detectors	18
12.1	General	18
12.2	Suitability	19
12.3	Function of gas detector	19
12.4	Ambient conditions, temperature and humidity	19
12.5	Typical measuring ranges and thresholds	20
12.6	Accuracy and performance	21
12.7	Response time	21
13	Test apparatus for fixed gas detectors	22
13.1	General	22
13.2	Apparatus no. 3b: Chamber with monitored concentration	22
13.3	Apparatus no. 4: Calibration gas with specific concentration	23
13.4	Apparatus no. 5: Calibration gas for aspirated systems	24
14	Performance tests of gas detector	24
14.1	General	24
14.2	Test conditions -- Temperature and humidity	24
14.3	Test methods	25
14.3.1	General	25
14.3.2	Test of accuracy and thresholds	25
14.3.3	Test of response time	25
15	Fixed gas detector characteristics, reporting of test results -- Reporting of test results ...	25
16	Service and maintenance -- Fixed gas detectors	25
16.1	Expected sensor lifecycle	25
16.2	Periodic check and calibration	25
17	Technical specification and product information - Fixed gas detectors	26
Annex A (informative) Conversion factors of leakage rate units		27
Annex B (informative) Correlation between test gas concentration and leakage rate		28
B.1	EXAMPLE 1a: Conversion of a concentration increase in a hood to a total leakage volume flow rate (pV-throughput)	28
B.2	EXAMPLE 1b: Concentration increase due to a small leak in a voluminous room	28
B.3	EXAMPLE 2: Conversion of a leakage rate (pV-throughput) into a mass flow rate	29
B.4	EXAMPLE 3: Calculation of the concentrations of tracer gas to be detected in front of a leak with specified leakage rate	30
Annex C (informative) Guidelines for application of Fixed Gas Detectors		32
Annex D (informative) Calculation of gas concentration from kg/m ³ to ppm		33
Annex E (informative) Selectivity, cross interference and potential contaminants		34
Bibliography		36