DIN EN 1397:2022-03 (E)

Heat exchangers - Hydronic room fan coil units - Test procedures for establishing the performance

Contents

Page

European foreword 4

1 Scope 5

2 Normative references 5

3 Terms and definitions 5

4 Designation of fan coil units 7

5 Symbols 7

6 Air flow rate test for ducted units 8
6.1 General conditions 8
6.2 Test installation 8
6.2.1 Outlet measurement method 8
6.2.2 Inlet measurement method 9
6.3 Pressure settings 10
6.4 Standard rating conditions 11
6.5 Test procedure 11
6.6 Data to be recorded 12

7 Capacity rating tests 13
7.1 General conditions 13
7.2 Test room 13
7.3 Installation of the test object 13
7.4 Standard rating conditions 13
7.4.1 Air flow conditions 13
7.4.2 Temperature conditions 14
7.4.3 Electrical conditions 14
7.5 Test method 14
7.5.1 General 14
7.5.2 Cooling capacity 15
7.5.3 Total heating capacity 16
7.5.4 Total electric power input 16
7.6 Measurements criteria 16
7.6.1 Air inlet dry bulb temperature 16
7.6.2 Moisture content 17
7.6.3 Liquid temperature 17
7.6.4 Liquid pressure 17
7.6.5 Condensate flow rate 17
7.6.6 Steady-state conditions 17
7.7 Uncertainties of measurement from indicated values 18
7.8 Test duration 19
7.9 Data to be recorded 19

8 Operating tests 20
8.1 General 20
8.2 Test conditions 20
8.3 Sweat test 20
8.4 Condensate disposal test 21

9 Test report 21
9.1 General information 21
9.2 Additional information 21
9.3 Test results 21

10 Manufacturer's data 22

Annex A (informative) Drawings of the different types of configurations of fan coil units 23

A.1 General 23
A.2 Non ducted units 23
A.3 Ducted units 24

Annex B (informative) Air flow rate test for non-ducted units 26

B.1 General conditions 26
B.2 Testing equipment 26
B.3 Test installation 26
B.4 Standard rating conditions 26
B.5 Test procedure 26
B.6 Data to be recorded 27

Annex C (normative) Design of separation partition for testing of cassette type fan coil units 28

C.1 General 28
C.2 1-way and 2-way cassette type 28
C.3 4-way cassette type 29

Annex ZA (informative) Relationship between this European Standard and the ecodesign requirements of Commission Regulation (EU) No 2016/2281 (OJEU L346/1-50, 20.12.2016) aimed to be covered 30