

# ISO 19454:2019 (E)

## Building environment design — Indoor environment — Daylight opening design for sustainability principles in visual environment

---

### Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Fundamentals
4.1	General
4.2	General principles of sustainability
4.3	Project information
4.4	Framework of generation and verification
4.5	Framework of documentation at approval
4.6	Harmonization of architectural and daylight opening design
5	Design elements of daylight openings
5.1	General
5.2	Matrix of aspects of daylight opening design
5.3	Daylight opening ratio to the wall area
5.4	Daylight opening ratio to the floor area
5.5	Levels of indoor daylight and the extent of sunlight
5.6	Quality of views to exterior
5.7	Daylight control systems in the building
6	Design process of daylight openings
6.1	General
6.2	Stage I — Formulation of project definition
6.2.1	Project definition
6.2.2	Output — Document I
6.2.3	Evaluation I
6.2.4	Output — Approval of document I
6.2.5	Iteration
6.3	Stage II – Schematic design
6.3.1	General
6.3.2	Input
6.3.3	Output
6.3.4	Evaluation II
6.3.5	Approval of document II
6.4	Stage III – Detailed design
6.4.1	General
6.4.2	Input
6.4.3	Output – Document IIIa
6.4.4	Analysis
6.4.5	Output – Document IIIb
6.4.6	Evaluation III
6.4.7	Approval of documents IIIa and IIIb
6.4.8	Iteration into detail design
6.5	Stage IV – Final design
6.5.1	General
6.5.2	Commissioning documents

- 6.5.3 Cost estimation
- 6.5.4 Output: the final documents

**Annex A (normative) Flow diagram of the design process**

**Annex B (informative) Basic architectural forms of the daylight opening**

- B.1 Side lighting
- B.2 Top lighting

**Annex C (informative) Matrix of aspects of daylight opening design**

**Annex D (informative) Matrix of output required to satisfy daylight opening design**

**Page count: 26**